





Benchmark Inspections, Inc. P.O. Box 1523 Hobe Sound, FL 33475 Phone: 888-984-4484

E-mail:cplaia@benchmarkinspectionpros.com

Wind Mitigation

Turtle Creek Association #1 Inc. 12 SE Concourse Dr Tequesta, FL 33469 October 10, 2023

Report Summary:

1. Building Code: C. Built 1971

2. Roof Covering: A. All roof coverings listed meet FBC Product Approval

3. Roof Deck Attchment: C. 8d nail 6" Max Spacing

4. Roof to Wall Attachment: B. Clips

5. Roof Geometry: A. Hip Roof

6. SWR: **B. No SWR**

7. Opening Protection Credit: X.

8. Construction Type: 100% Concrete/Masonry - 0% Wood Frame - 0% Other

NOTICE: This Report is in accordance with the CLIENT AGREEMENT, and is subject to the terms and conditions agreed upon therein. Upon receiving this report, Client agrees that it has been read in its entirety. Our inspection and this report have been performed with a written client agreement that limits its scope and usefulness. Unauthorized recipients are therefore advised not to rely upon this report, but rather to retain the services of an appropriately qualified home inspector of their choice to provide them with their own evaluation and report. Please note that the wall construction type in the report is an estimate and is included as a courtesy to your insurance agent or carrier which is classified between masonry/concrete, wood frame and/or other wall construction types.

Uniform Mitigation Verification Inspection Form

Maintain a copy of this form and any documentation provided with the insurance policy

Inspect	cion Date: October 10, 2023	or and form and any c	ocamenation prov	ded with the msurane	c poney			
	· Information							
	Name: Turtle Creek Associati	on #1 Inc		Contact Person:				
	s: 12 SE Concourse Dr	011 # 1 1110.		Home Phone:				
	equesta	Work Phone:						
	∕: Martin	Zip: 33469		Cell Phone:				
	nce Company:			Policy #:				
	f Home: 1971	# of Stories: 2		Email:				
accom though	: Any documentation used in pany this form. At least one part. The insurer may ask additional to the control of	hotograph must accompational questions regardin	any this form to valid g the mitigated featur	ate each attribute marked re(s) verified on this form	l in questions 3			
	ilding Code: Was the structure HVHZ (Miami-Dade or Browa	rd counties), South Florida	Building Code (SFBC	2-94)?				
	A. Built in compliance with the FBC: Year Built For homes built in 2002/2003 provide a permit application with a date after 3/1/2002: Building Permit Application Date (MM/DD/YYYY)							
	B. For the HVHZ Only: Built i provide a permit application w							
\times	C. Unknown or does not meet							
OR	of Covering: Select all roof covering: Year of Original Installation/Rering identified.				nce for each roof			
	2.1 Roof Covering Type:	Permit Application Date	FBC or MDC Product Approval #	Year of Original Installation or Replacement	No Information Provided for Compliance			
	1. Asphalt/Fiberglass Shingle							
	2. Concrete/Clay Tile	08/06/08	2008080371	2008				
	3. Metal				$\overline{\Box}$			
	4. Built Up							
	■ 5. Membrane	08/06/08	2008080371	2008				
	6. Other							
	6. Other				Ш			
\square	A. All roof coverings listed ab- installation OR have a roofing B. All roof coverings have a M roofing permit application afte	permit application date on liami-Dade Product Appro	or after 3/1/02 OR the val listing current at tir	roof is original and built in me of installation OR (for the	2004 or later. ne HVHZ only) a			
	C. One or more roof coverings	do not meet the requirement	ents of Answer "A" or "	"B".				
	D. No roof coverings meet the	requirements of Answer ".	A" or "B".					
3. Ro	of Deck Attachment: What is t	he weakest form of roof do	eck attachment?					
 A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the fieldOR- Batten decking supporting wood shakes or wood shinglesOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift less than that required for Options B or C below. B. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 								
	24"inches o.c.) by 8d common nails spaced a maximum of 12" inches in the fieldOR- Any system of screws, nails, adhesive other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d nails space a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf.							
X	C. Plywood/OSB roof sheathin 24"inches o.c.) by 8d common decking with a minimum of 2	nails spaced a maximum nails per board (or 1 nail p	of 6" inches in the fiel per board if each board	dOR- Dimensional lumb is equal to or less than 6 in	er/Tongue & Groove			
Inspec	tors Initials <u>CP</u> Property A	ddress_12 SE Concours	е Di Tequesta, FL 33	D 1 U3				

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

position requirements of C or D, but is secured with a minimum of 3 nails. C. Single Wraps Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side. D. Double Wraps Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side. E. Structural Anchor bolts structurally connected or reinforced concrete roof. F. Other: G. Unknown or unidentified H. No attic access 5. Roof Geometry: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification). A. Hip Roof Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: feet; Total roof system perimeter. Total length of non-hip features: feet; Total roof system perimeter: sq ft; Total roof area has a roof slope of less than 2:12 sq ft; Total roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area has a roof slope of less than 2:12. Roof area with sl				of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent sistance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at least						
F. Unknown or unidentified. G. No attic access.			-	ed Concrete Roof Deck.						
G. No attic access.			E. Other:							
4. Roof to Wall Attachment: What is the WEAKEST roof to wall connection? (Do not include attachment of hip/valley jacks within 5 lect of the inside or outside corner of the roof in determination of WEAKEST type) A. Toe Nails Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or determination of metal to momentors are: Secured to truss/rafter with a minimum of three (3) nails, and Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion. B. Clips Metal connectors that do not wrap over the top of the truss/rafter, and free of visible severe corrosion. Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails. C. Single Wraps Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side. D. Double Wraps Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side. D. E. Structural Anchor bolts structurally connected or reinforced concrete roof. F. Other: G. Unknown or unidentified H. No attic access 8. Roof Geometry: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification). A. Hip Roof Hip roof with no other roof shapes greater than 10% of the total r			F. Unknown or unidentified.							
5 feet of the inside or outside corner of the roof in determination of WEAKEST type) A. Toe Nails Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or Metal connectors that do not meet the minimal conditions or requirements of B, C, or D Minimal conditions to qualify for categories B, C, or D. All visible metal connectors are: Secured to truss/rafter with a minimum of three (3) nails, and Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corresion. B. Clips Metal connectors that do not wrap over the top of the truss/rafter, and free of visible severe corresion. C. Single Wraps Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails. C. Single Wraps Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side. D. Double Wraps Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side. D. Bouble Wraps Metal Connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, and is secured with a minimum of 2 nails on the front side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, on the frame of the proof secured to the opposing side, and a minimum of 1 na			G. No attic a	access.						
Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or Metal connectors that do not meet the minimal conditions or requirements of B, C, or D	4.									
the top plate of the wall, or Metal connectors that do not meet the minimal conditions or requirements of B, C, or D Minimal conditions to qualify for categories B, C, or D, All visible metal connectors are:		Ш	A. Toe Nails							
Minimal conditions to qualify for categories B, C, or D. All visible metal connectors are:										
Secured to truss/rafter with a minimum of three (3) nails, and Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ⅓ gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion. B. Clips Metal connectors that do not wrap over the top of the truss/rafter, or Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails. C. Single Wraps Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side. D. Double Wraps Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side. E. Structural F. Other: G. Unknown or unidentified H. No attic access S. Roof Geometry: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification). A. Hip Roof Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: 0feet; Total roof system perimeter: Total length				Metal connectors that do not meet the minimal conditions or requirements of B, C, or D						
Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion. B. Clips Metal connectors that do not wrap over the top of the truss/rafter, or Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails. C. Single Wraps Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side. D. Double Wraps Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or Metal Connectors consisting of a single strap that wraps over the top of the truss/rafter is secured to the wall on both sides, and is secured to the top plate with a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on each side. E. Structural Anchor bolts structurally connected or reinforced concrete roof. F. Other: G. Unknown or unidentified H. No attie access S. Roof Geometry: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification). A. Hip		Mir	nimal conditio	ons to qualify for categories B, C, or D. All visible metal connectors are:						
the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion. B. Clips			\times	Secured to truss/rafter with a minimum of three (3) nails, and						
Metal connectors that do not wrap over the top of the truss/rafter, or Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails. C. Single Wraps Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side. D. Double Wraps Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side. E. Structural Anchor bolts structurally connected or reinforced concrete roof. F. Other:			\boxtimes	the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe						
Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails. C. Single Wraps Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side. D. Double Wraps Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side. E. Structural F. Other: G. Unknown or unidentified H. No attic access S. Roof Geometry: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification). A. Hip Roof Hip roof with no other roof shapes greater than 10% of the total roof system perimeter: Total length of non-hip features: 0		\times	B. Clips							
position requirements of C or D, but is secured with a minimum of 3 nails. C. Single Wraps Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side. D. Double Wraps Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured to the wall on the secured with a minimum of three nails on each side. Restricted Anchor				Metal connectors that do not wrap over the top of the truss/rafter, or						
Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side. D. Double Wraps Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side. E. Structural Anchor bolts structurally connected or reinforced concrete roof. F. Other: G. Unknown or unidentified H. No attic access 5. Roof Geometry: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification). A. Hip Roof Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: 0 feet; Total roof system perimeter. Total length of non-hip features: 0 feet; Total roof system perimeter. Total length of non-hip features: 0 feet; Total roof system perimeter. Any roof that does not qualify as either (A) or (B) above. 6. Secondary Water Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss. B. No SWR. C. Unknown or undetermined. Inspectors Initials CP Property Address 12 SE Concourse Dr Tequesta, FL 33469			\boxtimes	Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails.						
D. Double Wraps Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side. E. Structural Anchor bolts structurally connected or reinforced concrete roof. F. Other: G. Unknown or unidentified H. No attic access S. Roof Geometry: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification). X A. Hip Roof Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: 0			C. Single Wi	Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a						
Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side. E. Structural Anchor bolts structurally connected or reinforced concrete roof. F. Other: G. Unknown or unidentified H. No attic access Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side. F. Other: G. Unknown or unidentified H. No attic access G. Unknown or unidentified H. No attic access A. Hip Roof Hip roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification). A. Hip Roof Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: 0 feet; Total roof system perimeter: 425 feet Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft C. Other Roof Any roof that does not qualify as either (A) or (B) above. A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss. B. No SWR. C. Unknown or undetermined.		П	D. Double W							
Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side. E. Structural Anchor bolts structurally connected or reinforced concrete roof. F. Other: G. Unknown or unidentified H. No attic access Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side. A. Hore G. Unknown or unidentified H. No attic access A. Hip Roof Hip roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification). A. Hip Roof Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: 0 feet; Total roof system perimeter: 425 feet B. Flat Roof Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft C. Other Roof Any roof that does not qualify as either (A) or (B) above. 6. Secondary Water Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss. B. No SWR. C. Unknown or undetermined. Inspectors Initials CP Property Address 12 SE Concourse Dr Tequesta, FL 33469				Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with						
 F. Other:										
 G. Unknown or unidentified H. No attic access 5. Roof Geometry: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification). ✓ A. Hip Roof Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: 0 feet; Total roof system perimeter: 425 feet ✓ B. Flat Roof Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft ✓ C. Other Roof Any roof that does not qualify as either (A) or (B) above. 6. Secondary Water Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) ✓ A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss. ✓ B. No SWR. ✓ C. Unknown or undetermined. Inspectors Initials CP Property Address 12 SE Concourse Dr Tequesta, FL 33469 				•						
 H. No attic access 5. Roof Geometry: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification). ☑ A. Hip Roof Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: 0 feet; Total roof system perimeter: 425 feet Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft ☐ C. Other Roof Any roof that does not qualify as either (A) or (B) above. 6. Secondary Water Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss. ☑ B. No SWR. ☐ C. Unknown or undetermined. Inspectors Initials CP Property Address 12 SE Concourse Dr Tequesta, FL 33469 										
the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification). A. Hip Roof										
Total length of non-hip features: O feet; Total roof system perimeter: 425 feet Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft C. Other Roof Any roof that does not qualify as either (A) or (B) above. 6. Secondary Water Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss. B. No SWR. C. Unknown or undetermined. Inspectors Initials CP Property Address 12 SE Concourse Dr Tequesta, FL 33469	5.									
□ B. Flat Roof Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft □ C. Other Roof Any roof that does not qualify as either (A) or (B) above. 6. Secondary Water Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) □ A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss. ☑ B. No SWR. □ C. Unknown or undetermined. Inspectors Initials CP Property Address 12 SE Concourse Dr Tequesta, FL 33469		\boxtimes	A. Hip Roof	• • • • • • • • • • • • • • • • • • • •						
 C. Other Roof Any roof that does not qualify as either (A) or (B) above. 6. Secondary Water Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss. ☑ B. No SWR. ☐ C. Unknown or undetermined. Inspectors Initials CP Property Address 12 SE Concourse Dr Tequesta, FL 33469 			B. Flat Roof	Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of						
 A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss. B. No SWR. C. Unknown or undetermined. Inspectors Initials CP Property Address 12 SE Concourse Dr Tequesta, FL 33469 			C. Other Roo							
	6.	<u>Sec</u> □	A. SWR (also sheathing dwelling) B. No SWR.	so called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the from water intrusion in the event of roof covering loss.						
*This varification form is valid for up to five (5) years provided no metarial changes have been made to the structure or	In	spec	tors Initials _	CP Property Address 12 SE Concourse Dr Tequesta, FL 33469						
This verification form is valid for up to five (3) years provided no material changes have been made to the structure or	*T	his v	verification fo	orm is valid for up to five (5) years provided no material changes have been made to the structure or						

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

7. Opening Protection: What is the weakest form of wind borne debris protection installed on the structure? First, use the table to determine the weakest form of protection for each category of opening. Second, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings and (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable. Non-Glazed **Opening Protection Level Chart Glazed Openings** Openings Place an "X" in each row to identify all forms of protection in use for each Windows opening type. Check only one answer below (A thru X), based on the weakest Garage Glass Entry Garage or Entry Skylights form of protection (lowest row) for any of the Glazed openings and indicate **Doors Block** Doors **Doors** Doors the weakest form of protection (lowest row) for Non-Glazed openings. Not Applicable- there are no openings of this type on the structure Α Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights) В Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights) С Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007 Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E D 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance Opening Protection products that appear to be A or B but are not verified Ν Other protective coverings that cannot be identified as A, B, or C No Windborne Debris Protection Х A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level A in the table above). Miami-Dade County PA 201, 202, and 203 Florida Building Code Testing Application Standard (TAS) 201, 202, and 203 American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996 Southern Standards Technical Document (SSTD) 12 For Skylights Only: ASTM E 1886 and ASTM E 1996 For Garage Doors Only: ANSI/DASMA 115 A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist LA.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or X in the table above A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All Glazed openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level B in the table above): ASTM E 1886 and ASTM E 1996 (Large Missile - 4.5 lb.) SSTD 12 (Large Missile – 4 lb. to 8 lb.) For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large Missile - 2 to 4.5 lb.) ☐ B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above L C. Exterior Opening Protection- Wood Structural Panels meeting FBC 2007 All Glazed openings are covered with plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above). LC.1 All Non-Glazed openings classified as A, B, or C in the table above, or no Non-Glazed openings exist LC.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in the table above C.3 One or More Non-Glazed openings is classified as Level N or X in the table above Inspectors Initials CP Property Address 12 SE Concourse Dr Tequesta, FL 33469

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

N. Exterior Opening Protection (unverified shutter s protective coverings not meeting the requirements of Ar with no documentation of compliance (Level N in the ta	nswer "A", "B", or C" or systems that	
N.1 All Non-Glazed openings classified as Level A, B, C, o	/	Lonenings evist
N.2 One or More Non-Glazed openings classified as Level 1 table above		• •
N.3 One or More Non-Glazed openings is classified as Leve	el X in the table above	
X. None or Some Glazed Openings One or more Glazed	ed openings classified and Level X in	n the table above.
MITIGATION INSPECTIONS MUST B Section 627.711(2), Florida Statutes, provi	~	
Qualified Inspector Name: CHARLIE PLAIA	License Type: HOME INSPECTOR	License or Certificate #: HI 4860
Inspection Company: BENCHMARK INSPECTIONS, INC	Phone: 88	38-984-4484
Qualified Inspector – I hold an active license as a	: (check one)	
Home inspector licensed under Section 468.8314, Florida Statute training approved by the Construction Industry Licensing Board	es who has completed the statutory numb and completion of a proficiency exam.	er of hours of hurricane mitigation
Building code inspector certified under Section 468.607, Florida		
General, building or residential contractor licensed under Section		
Professional engineer licensed under Section 471.015, Florida St		
Professional architect licensed under Section 481.213, Florida St		
Any other individual or entity recognized by the insurer as posse verification form pursuant to Section 627.711(2), Florida Statute.		perly complete a uniform mitigation
(print name) contractors and professional engineers only) I had my emploand I agree to be responsible for his/her work. Qualified Inspector Signature:	ructures personally and not through ect employee who possesses the regard and I personally performed the inspoyee () per (print name of inspector) Date: 10/10/2023	th employees or other persons. quisite skill, knowledge, and pection or (licensed form the inspection
An individual or entity who knowingly or through gross ne subject to investigation by the Florida Division of Insurance appropriate licensing agency or to criminal prosecution. (Secretifies this form shall be directly liable for the misconduct performed the inspection.	e Fraud and may be subject to adn ection 627.711(4)-(7), Florida Statu	ninistrative action by the ttes) The Qualified Inspector who
<u>Homeowner to complete</u> : I certify that the named Qualified residence identified on this form and that proof of identification		
Signature:I	Date: 10/10/2023	
An individual or entity who knowingly provides or utters a obtain or receive a discount on an insurance premium to w of the first degree. (Section 627.711(7), Florida Statutes)		
The definitions on this form are for inspection purposes on as offering protection from hurricanes.	ly and cannot be used to certify an	y product or construction feature
Inspectors Initials CP Property Address 12 SE Concour	se Dr Tequesta, FL 33469	
*This verification form is valid for up to five (5) years prov	ided no material changes have bee	n made to the structure or

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155

Page 4 of 4

Click any of the results below to view more details.

Showing 1-10 of 10 | Download results

/110 vv	ing 1-10 of 10	Download results								
	Application Date	Record Number	Record Type	Address	Action	<u>Status</u>	<u>Project</u> <u>Name</u>	<u>Description</u>	Expiration Date	Kiva Hist T #
	06/20/2023	BLD2023061169	Heating-A/C- Refrig Residential Changeout	12 SE CONCOURSE DR, E, JUPITER FL 33469		Closed-Certificate Issued		replace ac equipment like for like		
	04/18/2023	BLD2023040858	Commercial Shutters	12 SE CONCOURSE DR, F, JUPITER FL 33469		Closed-Certificate Issued		Furnish and install HV Bertha Accordion Shutters to 2 openings.		
	04/17/2023	BLD2023040807	Residential Shutters	12 SE CONCOURSE DR, F, JUPITER FL 33469		Closed-Cancelled		Furnish and install HV Bertha Accordion Shutters to 2 openings.		
	08/31/2015	BACC2015090116	Heating-A/C- Refrig- Commercial Changeout	12 SE CONCOURSE DR, B, JUPITER FL 33469-1541		DONE	BLDG 12 APT B - HELEN COUGHTER	2.5 ton a/c change out with a 8 kw heat strip exact change out		T17295
	06/10/2013	BSUC2013060673	Commercial Shutters	12 SE CONCOURSE DR, E, JUPITER FL 33469-1541		DONE		Install 1 opening accordion shutter and 1 opening armor screen		T14639
	08/23/2010	BSHU2010090103	Residential Shutters	12 SE CONCOURSE DR, B, JUPITER FL 33469-1541		DONE		INSTALL 5 ACCORDION SHUTTERS		T11964
	08/06/2008	BRR2008080371	Residential Roofing	12 SE CONCOURSE DR, F, JUPITER FL 33469-1541		DONE	TURTLE CREEK	RE ROOF TILE & FLAT- BUILDING 12- COMMERCIAL		T10596
			Residential	12 SE CONCOURSE				INSTALL ACCORDION		
	11/08/2006	BSHU2006110469	Shutters	DR, B, JUPITER FL 33469-1541		CNCL		SHUTTERS ON 3 OPENINGS		T91488
	05/30/2001	BMICT29033	Commercial Miscellaneous	12 SE CONCOURSE DR, D, JUPITER FL 33469-1541	Pay Fees Due	VOID		balcony repair (concrete) for multi family, 6 units- BLDG 12		
	01/27/1992	BAC92010336	Heating-A/C- Refrig Residential Changeout	12 SE CONCOURSE DR, E, JUPITER FL 33469-1541		DONE				

Martin County Florida Your County. Your Community.

2401 SE Monterey Road, Stuart, FL 34996

Phone (772) 288-5400





Front Elevation



Rear Elevation



8d Nails



Right Elevation



Left Elevation



19/32" Sheathing





6" Max Spacing



6" Max Spacing



6" Max Spacing



Clips



Clips



Truss 24" O.C.





Building 12