





Benchmark Inspections, Inc. P.O. Box 1523 Hobe Sound, FL 33475 Phone: 888-984-4484

E-mail:cplaia@benchmarkinspectionpros.com

Wind Mitigation

Turtle Creek Association #1 Inc. 9 SE Turtle Creek Dr Tequesta, FL 33469 October 10, 2023

Report Summary:

1. Building Code: C. Built 1971

2. Roof Covering: A. All roof coverings listed meet FBC Product Approval

3. Roof Deck Attchment: C. 8d nail 6" Max Spacing

4. Roof to Wall Attachment: B. Clips

5. Roof Geometry: A. Hip Roof

6. SWR: **B. No SWR**

7. Opening Protection Credit: X.

8. Construction Type: 100% Concrete/Masonry - 0% Wood Frame - 0% Other

NOTICE: This Report is in accordance with the CLIENT AGREEMENT, and is subject to the terms and conditions agreed upon therein. Upon receiving this report, Client agrees that it has been read in its entirety. Our inspection and this report have been performed with a written client agreement that limits its scope and usefulness. Unauthorized recipients are therefore advised not to rely upon this report, but rather to retain the services of an appropriately qualified home inspector of their choice to provide them with their own evaluation and report. Please note that the wall construction type in the report is an estimate and is included as a courtesy to your insurance agent or carrier which is classified between masonry/concrete, wood frame and/or other wall construction types.

Uniform Mitigation Verification Inspection Form

Maintain a copy of this form and any documentation provided with the insurance policy

т		or this form and any a	ocamenation provi	ided with the msurane	c poney		
	ion Date: October 10, 2023						
	Information	#A 1		Control D			
	Name: Turtle Creek Association	on #1 Inc.		Contact Person: Home Phone:			
	s: 9 SE Turtle Creek Dr	[7]					
	equesta	Zip: 33469		Work Phone:			
	: Martin			Cell Phone:			
	ce Company:			Policy #:			
Year of	Home: 1971	# of Stories: 2		Email:			
accom	: Any documentation used in pany this form. At least one plots. The insurer may ask addit	notograph must accompa	any this form to valida	ite each attribute marked	in questions 3		
	Iding Code: Was the structure I HVHZ (Miami-Dade or Browar	d counties), South Florida	Building Code (SFBC-	-94)?			
Ш	A. Built in compliance with the a date after 3/1/2002: Building			n 2002/2003 provide a peri	nit application with		
	B. For the HVHZ Only: Built in provide a permit application wi						
\times	C. Unknown or does not meet to	he requirements of Answe	r "A" or "B"				
2. Roof Covering: Select all roof covering types in use. Provide the permit application date OR FBC/MDC Product Approval number OR Year of Original Installation/Replacement OR indicate that no information was available to verify compliance for each roof covering identified.							
	2.1 Roof Covering Type:	Permit Application Date	FBC or MDC Product Approval #	Year of Original Installation or Replacement	No Information Provided for Compliance		
	1. Asphalt/Fiberglass Shingle	//					
	2. Concrete/Clay Tile	08/06/08	2008080390	2008	П		
	3. Metal						
	_	/					
	4. Built Up	//	2008080390	2008	님		
	5. Membrane	08/06/08	2006060390	2000			
	6. Other	/					
 A. All roof coverings listed above meet the FBC with a FBC or Miami-Dade Product Approval listing current at time of installation OR have a roofing permit application date on or after 3/1/02 OR the roof is original and built in 2004 or later. B. All roof coverings have a Miami-Dade Product Approval listing current at time of installation OR (for the HVHZ only) a roofing permit application after 9/1/1994 and before 3/1/2002 OR the roof is original and built in 1997 or later. 							
	C. One or more roof coverings	do not meet the requirement	nts of Answer "A" or "	В".			
	D. No roof coverings meet the 1	requirements of Answer "A	A" or "B".				
3. Roo	of Deck Attachment: What is th	e weakes t form of roof de	ck attachment?				
	A. Plywood/Oriented strand bo by staples or 6d nails spaced at shinglesOR- Any system of s mean uplift less than that requir B. Plywood/OSB roof sheathin 24"inches o.c.) by 8d common other deck fastening system or	ard (OSB) roof sheathing at 6" along the edge and 12 crews, nails, adhesives, of the for Options B or C belong with a minimum thickness spaced a maximum contruss/rafter spacing that is	attached to the roof true 2" in the fieldOR- Bather deck fastening systow. ess of 7/16" inch attache of 12" inches in the fiel shown to have an equi	atten decking supporting very or truss/rafter spacing to the roof truss/rafter (s.dOR- Any system of screvalent or greater resistance	yood shakes or wood hat has an equivalent paced a maximum of ews, nails, adhesives,		
	a maximum of 12 inches in the C. Plywood/OSB roof sheathin 24"inches o.c.) by 8d common decking with a minimum of 2 roors Initials CP Property Ac	g with a minimum thickne nails spaced a maximum ails per board (or 1 nail p	ess of 7/16"inch attaches of 6" inches in the field er board if each board	ed to the roof truss/rafter (s dOR- Dimensional lumb is equal to or less than 6 in	er/Tongue & Groove		
mspec	tors initials <u> </u>	iui css_	5. 15445514, 1 2 00				

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

		of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent istance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at least							
	D. Reinforce	d Concrete Roof Deck.							
닏		or unidentified.							
Ш	G. No attic a	ccess.							
	of to Wall Attachment: What is the <u>WEAKEST</u> roof to wall connection? (Do not include attachment of hip/valley jacks within et of the inside or outside corner of the roof in determination of WEAKEST type)								
Ш	A. Toe Nails								
	Ш	Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or							
		Metal connectors that do not meet the minimal conditions or requirements of B, C, or D							
Minimal conditions to qualify for categories B, C, or D. All visible metal connectors are:									
	\boxtimes	Secured to truss/rafter with a minimum of three (3) nails, and							
	\boxtimes	Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion.							
\boxtimes	B. Clips								
		Metal connectors that do not wrap over the top of the truss/rafter, or							
	\boxtimes	Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails.							
	C. Single Wr	•							
		Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side.							
	D. Double W	Vraps							
		Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or							
		Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side.							
	E. Structural	Anchor bolts structurally connected or reinforced concrete roof.							
	F. Other:								
	G. Unknown	or unidentified							
	H. No attic access								
		What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification).							
\boxtimes	A. Hip Roof								
	B. Flat Roof	Total length of non-hip features: 0 feet; Total roof system perimeter: 425 feet Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of							
	C. Other Roc	less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft							
Ш	C. Offici Roc	Any root that does not qualify as either (A) of (B) above.							
6. <u>Sec</u>	A. SWR (also sheathing dwelling f B. No SWR.	r Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) o called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the from water intrusion in the event of roof covering loss. or undetermined.							
Inspec	tors Initials _	Property Address 9 SE Turtle Creek Dr Tequesta, FL 33469							
*This	verification fo	orm is valid for up to five (5) years provided no material changes have been made to the structure or							

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

7. Opening Protection: What is the weakest form of wind borne debris protection installed on the structure? First, use the table to determine the weakest form of protection for each category of opening. Second, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings and (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable. Non-Glazed **Opening Protection Level Chart Glazed Openings Openings** Place an "X" in each row to identify all forms of protection in use for each Windows opening type. Check only one answer below (A thru X), based on the weakest Garage Glass Entry Garage or Entry Skylights form of protection (lowest row) for any of the Glazed openings and indicate **Doors Block** Doors **Doors** Doors the weakest form of protection (lowest row) for Non-Glazed openings. Not Applicable- there are no openings of this type on the structure Α Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights) В Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights) С Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007 Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E D 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance Opening Protection products that appear to be A or B but are not verified Ν Other protective coverings that cannot be identified as A, B, or C No Windborne Debris Protection Х A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level A in the table above). Miami-Dade County PA 201, 202, and 203 Florida Building Code Testing Application Standard (TAS) 201, 202, and 203 American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996 Southern Standards Technical Document (SSTD) 12 For Skylights Only: ASTM E 1886 and ASTM E 1996 For Garage Doors Only: ANSI/DASMA 115 A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist LA.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or X in the table above A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All Glazed openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level B in the table above): ASTM E 1886 and ASTM E 1996 (Large Missile - 4.5 lb.) SSTD 12 (Large Missile – 4 lb. to 8 lb.) For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large Missile - 2 to 4.5 lb.) ☐ B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above L C. Exterior Opening Protection- Wood Structural Panels meeting FBC 2007 All Glazed openings are covered with plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above). LC.1 All Non-Glazed openings classified as A, B, or C in the table above, or no Non-Glazed openings exist LC.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in the table above C.3 One or More Non-Glazed openings is classified as Level N or X in the table above Inspectors Initials CP Property Address 9 SE Turtle Creek Dr Tequesta, FL 33469

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

N. Exterior Opening Protection (unverified shutter syprotective coverings not meeting the requirements of An with no documentation of compliance (Level N in the tall	swer "A", "B", or C" or syst	
N.1 All Non-Glazed openings classified as Level A, B, C, or	N in the table above, or no No	n-Glazed openings exist
N.2 One or More Non-Glazed openings classified as Level I table above	O in the table above, and no Nor	n-Glazed openings classified as Level X in the
N.3 One or More Non-Glazed openings is classified as Leve	l X in the table above	
X. None or Some Glazed Openings One or more Glaze	d openings classified and Le	evel X in the table above.
MITIGATION INSPECTIONS MUST B. Section 627.711(2), Florida Statutes, provi	des a listing of individuals w	who may sign this form.
Qualified Inspector Name: CHARLIE PLAIA	License Type: HOME INSPECTOR	License or Certificate #: HI 4860
Inspection Company: BENCHMARK INSPECTIONS, INC		Phone: 888-984-4484
Qualified Inspector – I hold an active license as a:	(check one)	
Home inspector licensed under Section 468.8314, Florida Statute training approved by the Construction Industry Licensing Board a		
Building code inspector certified under Section 468.607, Florida		
General, building or residential contractor licensed under Section		
Professional engineer licensed under Section 471.015, Florida Sta		
		so to muon culvi commulato o uniforma mitigation
Any other individual or entity recognized by the insurer as possess verification form pursuant to Section 627.711(2), Florida Statutes		is to properly complete a uniform mitigation
(print name) contractors and professional engineers only) I had my emplo and I agree to be responsible for his her work. Qualified Inspector Signature: An individual or entity who knowingly or through gross nessubject to investigation by the Florida Division of Insurance appropriate licensing agency or to criminal prosecution. (So certifies this form shall be directly liable for the misconduct performed the inspection. Homeowner to complete: I certify that the named Qualified residence identified on this form and that proof of identification Signature: An individual or entity who knowingly provides or utters a	uctures personally and not bet employee who possesses and I personally performed yee ((print name of inspection for the provides a false or error for the author of the provided to me or my and the provided to me or my	the requisite skill, knowledge, and the inspection or (licensed) perform the inspection tor) 2023 fraudulent mitigation verification form is t to administrative action by the da Statutes) The Qualified Inspector who horized mitigation inspector personally loyee did perform an inspection of the Authorized Representative.
obtain or receive a discount on an insurance premium to wl of the first degree. (Section 627.711(7), Florida Statutes)		
The definitions on this form are for inspection purposes onl as offering protection from hurricanes.	y and cannot be used to cer	ctily any product or construction feature
Inspectors Initials CP Property Address 9 SE Turtle Cre	ek Dr Tequesta, FL 33469)
*This verification form is valid for up to five (5) years provinaccuracies found on the form.	ided no material changes h	ave been made to the structure or
OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155		Page 4 of 4

Showing 1-10 of 16 | Download results

Application Date	Record Number	Record Type	<u>Address</u>	Action	<u>Status</u>	<u>Project</u> <u>Name</u>	<u>Description</u>	Expiration Date	<u>Kiva</u> Hist T #
05/16/2022	BLD2022050921	Commercial Miscellaneous	9 SE TURTLE CREEK DR, A, JUPITER FL 33469		Closed-Certificate Issued	Turtle Creek Condominiums	Asphalt milling, asphalt paving, and restriping Turtle Creek #1 Association, Inc. 195 Turtle Creek Drive, Tequesta, FL 33469		
06/11/2019	BLD2019060534	Commercial Shutters	9 SE TURTLE CREEK DR, E, JUPITER FL 33469-5511		Closed-Certificate Issued		FURNISH AND INSTALL HV BERTHA ACCORDION HURRICANE SHUTTER TO COVER OUTSIDE WALL OVER SCREENED PORCH BALCONY		
05/17/2019	BLD2019050927	Residential Shutters	9 SE TURTLE CREEK DR, F, JUPITER FL 33469-1532		Closed-Certificate Issued		install accordions on outside of patio		
03/12/2019	BLD2019030510	Residential Concrete Restoration	9 SE TURTLE CREEK DR, E, JUPITER FL 33469-5511		Closed-Certificate Issued	TURTLE CREEK CONDO ASSOC	COMMERCIAL- CONCRETE RESTORATION REPAIRS- SEE ENG'S SEPCIFICATIN bldg. 9 UNITS E&F		
08/03/2018	BLD2018080201	Commercial Electrical	9 SE TURTLE CREEK DR, F, JUPITER FL 33469-1532		Closed-Certificate Issued		PERMIT RENEWED ON 10/16/2020 FOR 6MO REPLACE EXISTING M.L.O. 30 CIR. 200a ELECT PANEL WITH. THE SAME 200A M.L.O. PANEL & NEW BREAKERS EXISTING PANEL IS BURNING UP THE BUSS		
07/25/2016	BAC2016081147	Heating-A/C- Refrig Residential Changeout	9 SE TURTLE CREEK DR, B, JUPITER FL 33469-1532		DONE		replace existing condensor with rheem ra1442aj1 3.5 ton 15 seer		T186112
12/03/2015	BAC2015120309	Heating-A/C- Refrig Residential Changeout	9 SE TURTLE CREEK DR, F, JUPITER FL 33469-1532		DONE		REPLACE A/C UNIT WITHOUT DUCT REPLACEMENT FOR RESIDENTIAL BUILDING		T176375
10/13/2015	BRR2015101057	Residential Roofing	9 SE TURTLE CREEK DR, TEQUESTA FL 33469-5511		DONE		REMOVE & REPLACE EXISTING SHINGLE ROOF		T174477
04/21/2009	BSHU2009040347	Residential Shutters	9 SE TURTLE CREEK DR, E, JUPITER FL 33469-5511		DONE		INSTALL 4 ACCORDION HURRICANE SHUTTERS		T109984
08/06/2008	BRR2008080390	Residential Roofing	9 SE TURTLE CREEK DR, TEQUESTA FL 33469-5511		DONE	TURTLE CREEK	RE ROOF TILE & FLAT- BUILDING 9- COMMERCIAL		T105999

Martin County Florida Your County. Your Community.

2401 SE Monterey Road, Stuart, FL 34996

Phone (772) 288-5400





Front Elevation





Rear Elevation



Left Elevation



8d Nails



19/32" Sheathing





6" Max Spacing



6" Max Spacing



6" Max Spacing



Clips





Truss 24" O.C.





Building 9