





Benchmark Inspections, Inc. P.O. Box 1523 Hobe Sound, FL 33475 Phone: 888-984-4484

E-mail:cplaia@benchmarkinspectionpros.com

## Wind Mitigation

Turtle Creek Association #1 Inc. 10 SE Turtle Creek Dr Tequesta, FL 33469 October 10, 2023

## **Report Summary:**

1. Building Code: C. Built 1971

2. Roof Covering: A. All roof coverings listed meet FBC Product Approval

3. Roof Deck Attchment: C. 8d nail 6" Max Spacing

4. Roof to Wall Attachment: **C. Single Wraps** 

5. Roof Geometry: A. Hip Roof

6. SWR: **B. No SWR** 

7. Opening Protection Credit: X.

8. Construction Type: 100% Concrete/Masonry - 0% Wood Frame - 0% Other

NOTICE: This Report is in accordance with the CLIENT AGREEMENT, and is subject to the terms and conditions agreed upon therein. Upon receiving this report, Client agrees that it has been read in its entirety. Our inspection and this report have been performed with a written client agreement that limits its scope and usefulness. Unauthorized recipients are therefore advised not to rely upon this report, but rather to retain the services of an appropriately qualified home inspector of their choice to provide them with their own evaluation and report. Please note that the wall construction type in the report is an estimate and is included as a courtesy to your insurance agent or carrier which is classified between masonry/concrete, wood frame and/or other wall construction types.

Uniform Mitigation Verification Inspection Form

Maintain a copy of this form and any documentation provided with the insurance policy

I · · ·		or and form and any t	accamenation pro	vided with the mourane	e poney			
	ion Date: October 10, 2023							
	Information	an #4 Inc		Control Down				
	Name: Turtle Creek Associati	on #1 Inc.		Contact Person:				
	s: 10 SE Turtle Creek Dr	7' 22'22		Home Phone:				
	equesta	Zip: 33469		Work Phone:				
	: Martin			Cell Phone:				
	ce Company:			Policy #:				
Year of	Home: 1971	# of Stories: 2		Email:				
accomp	: Any documentation used in pany this form. At least one p 7. The insurer may ask addi	hotograph must accomp	any this form to valid	late each attribute marked	l in questions 3			
	Iding Code: Was the structure HVHZ (Miami-Dade or Browa	rd counties), South Florida	a Building Code (SFB0	C-94)?				
Ш	A. Built in compliance with the a date after 3/1/2002: Building	Permit Application Date	(MM/DD/YYYY)					
	B. For the HVHZ Only: Built i provide a permit application w							
$\times$	C. Unknown or does not meet	the requirements of Answ	er "A" or "B"					
OR	2. Roof Covering: Select all roof covering types in use. Provide the permit application date OR FBC/MDC Product Approval number OR Year of Original Installation/Replacement OR indicate that no information was available to verify compliance for each roof covering identified.							
	2.1 Roof Covering Type:	Permit Application Date	FBC or MDC Product Approval #	Year of Original Installation or Replacement	No Information Provided for Compliance			
	1. Asphalt/Fiberglass Shingle	/ /						
	2. Concrete/Clay Tile	08/06/08	2008080389	2008	$\overline{\Box}$			
	3. Metal							
		/						
	4. Built Up		000000000	0000				
	X 5. Membrane	08/06/08	2008080389	2008				
	6. Other							
<ul> <li>A. All roof coverings listed above meet the FBC with a FBC or Miami-Dade Product Approval listing current at time of installation OR have a roofing permit application date on or after 3/1/02 OR the roof is original and built in 2004 or later.</li> <li>B. All roof coverings have a Miami-Dade Product Approval listing current at time of installation OR (for the HVHZ only) a roofing permit application after 9/1/1994 and before 3/1/2002 OR the roof is original and built in 1997 or later.</li> </ul>								
	C. One or more roof coverings	do not meet the requirem	ents of Answer "A" or	"B".				
	D. No roof coverings meet the	requirements of Answer '	'A" or "B".					
3. <b>Roc</b>	of Deck Attachment: What is t	he <u>weakest</u> form of roof d	leck attachment?					
	A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the fieldOR- Batten decking supporting wood shakes or wood shinglesOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift less than that required for Options B or C below.  B. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 12" inches in the fieldOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d nails spaced							
$\boxtimes$	a maximum of 12 inches in the C. Plywood/OSB roof sheathi: 24"inches o.c.) by 8d common	ng with a minimum thickr	ness of 7/16"inch attacl	hed to the roof truss/rafter (s				
Inspect	decking with a minimum of 2 tors Initials <u>CP</u> Property A	nails per board (or 1 nail j	per board if each board	d is equal to or less than 6 in				
1								

\*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

		Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at least 182 psf.								
		D. Reinforced Concrete Roof Deck.								
	E. Other:									
	or unidentified.									
	Ш	G. No attic a	access.							
4.		<b>vof to Wall Attachment:</b> What is the <b>WEAKEST</b> roof to wall connection? (Do not include attachment of hip/valley jacks within eet of the inside or outside corner of the roof in determination of WEAKEST type)								
	Ш	A. Toe Nails								
		Ш	Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or							
			Metal connectors that do not meet the minimal conditions or requirements of B, C, or D							
	Mir	nimal condition	ons to qualify for categories B, C, or D. All visible metal connectors are:							
		$\boxtimes$	Secured to truss/rafter with a minimum of three (3) nails, and							
		$\boxtimes$	Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter <b>and</b> blocked no more than 1.5" of the truss/rafter, <b>and</b> free of visible severe corrosion.							
		B. Clips								
			Metal connectors that do not wrap over the top of the truss/rafter, or							
			Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails.							
	$\times$	C. Single W	•							
			Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side.							
		D. Double V	Vraps							
		Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured w a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or								
			Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side.							
		E. Structural	Anchor bolts structurally connected or reinforced concrete roof.							
	$\sqcup$	F. Other:								
	닏		or unidentified							
	Ш	H. No attic access								
5.			What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification).							
	$\times$	A. Hip Roof								
	П	B. Flat Roof	Total length of non-hip features: 0 feet; Total roof system perimeter: 425 feet  Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of							
		C. Other Roo	less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft of Any roof that does not qualify as either (A) or (B) above.							
6.	Sec	A. SWR (also sheathing dwelling) B. No SWR.	r Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) to called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the from water intrusion in the event of roof covering loss.							
Ins	spec	tors Initials _	CP_Property Address_10 SE Turtle Creek Dr Tequesta, FL 33469							
*T	'hia -	varification fo	orm is valid for up to five (5) years provided no material changes have been made to the structure or							
1	1113	, ci iiicativii 10	ram is rame for up to five (3) years provided no material changes have been made to the structure of							

<sup>\*</sup>This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

7. Opening Protection: What is the weakest form of wind borne debris protection installed on the structure? First, use the table to determine the weakest form of protection for each category of opening. Second, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings and (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable. Non-Glazed **Opening Protection Level Chart Glazed Openings** Openings Place an "X" in each row to identify all forms of protection in use for each Windows opening type. Check only one answer below (A thru X), based on the weakest Garage Glass Entry Garage or Entry Skylights form of protection (lowest row) for any of the Glazed openings and indicate **Doors Block** Doors **Doors** Doors the weakest form of protection (lowest row) for Non-Glazed openings. Not Applicable- there are no openings of this type on the structure Α Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights) В Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights) С Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007 Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E D 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance Opening Protection products that appear to be A or B but are not verified Ν Other protective coverings that cannot be identified as A, B, or C No Windborne Debris Protection Х A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level A in the table above). Miami-Dade County PA 201, 202, and 203 Florida Building Code Testing Application Standard (TAS) 201, 202, and 203 American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996 Southern Standards Technical Document (SSTD) 12 For Skylights Only: ASTM E 1886 and ASTM E 1996 For Garage Doors Only: ANSI/DASMA 115 A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist LA.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or X in the table above A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All Glazed openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level B in the table above): ASTM E 1886 and ASTM E 1996 (Large Missile - 4.5 lb.) SSTD 12 (Large Missile – 4 lb. to 8 lb.) For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large Missile - 2 to 4.5 lb.) ☐ B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above L C. Exterior Opening Protection- Wood Structural Panels meeting FBC 2007 All Glazed openings are covered with plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above). LC.1 All Non-Glazed openings classified as A, B, or C in the table above, or no Non-Glazed openings exist LC.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in the table above C.3 One or More Non-Glazed openings is classified as Level N or X in the table above Inspectors Initials CP Property Address 10 SE Turtle Creek Dr Tequesta, FL 33469

<sup>\*</sup>This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

N. Exterior Opening Protection (unverified shutter syprotective coverings not meeting the requirements of An with no documentation of compliance (Level N in the tal	swer "A", "B", or C" or syst						
N.1 All Non-Glazed openings classified as Level A, B, C, or	,	n-Glazed openings exist					
N.2 One or More Non-Glazed openings classified as Level I table above							
N.3 One or More Non-Glazed openings is classified as Leve	l X in the table above						
X. None or Some Glazed Openings One or more Glaze	d openings classified and Le	evel X in the table above.					
MITIGATION INSPECTIONS MUST B. Section 627.711(2), Florida Statutes, provid	~	who may sign this form.					
Qualified Inspector Name: CHARLIE PLAIA	License Type: HOME INSPECTOR	License or Certificate #: HI 4860					
Inspection Company: BENCHMARK INSPECTIONS, INC		Phone: 888-984-4484					
Qualified Inspector – I hold an active license as a:	(check one)						
Home inspector licensed under Section 468.8314, Florida Statute training approved by the Construction Industry Licensing Board a							
Building code inspector certified under Section 468.607, Florida							
General, building or residential contractor licensed under Section							
Professional engineer licensed under Section 471.015, Florida Sta Professional architect licensed under Section 481.213, Florida Sta							
Professional architect licensed under Section 481.213, Florida Sta  Any other individual or entity recognized by the insurer as posses		es to properly complete a uniform mitigation					
verification form pursuant to Section 627.711(2), Florida Statutes		is to properly complete a uniform minigation					
Individuals other than licensed contractors licensed under Section 489.111, Florida Statutes, or professional engineer licensed under Section 471.015, Florida Statues, must inspect the structures personally and not through employees or other persons. Licensees under s.471.015 or s.489.111 may authorize a direct employee who possesses the requisite skill, knowledge, and experience to conduct a mitigation verification inspection.  I, CHARLIE PLAIA am a qualified inspector and I personally performed the inspection or (licensed (print name) contractors and professional engineers only) I had my employee () perform the inspection and I agree to be responsible for his her work.  Qualified Inspector Signature:							
obtain or receive a discount on an insurance premium to whof the first degree. (Section 627.711(7), Florida Statutes)							
The definitions on this form are for inspection purposes onl as offering protection from hurricanes.	y and cannot be used to cer	rtify any product or construction feature					
Inspectors Initials CP Property Address 10 SE Turtle Cro	eek Dr Tequesta, FL 3346	69					
*This verification form is valid for up to five (5) years provinaccuracies found on the form.	ded no material changes h	ave been made to the structure or					
OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155		Page 4 of 4					

Click any of the results below to view more details.

Showing 11-20 of 25 | Download results

Application Date	Record Number	Record Type	<u>Address</u>	Action	<u>Status</u>	<u>Project</u> <u>Name</u>	Description	Expiration Date	Kiva Hist T#
03/20/2020	BLD2020031111	Commercial Shutters	10 SE TURTLE CREEK DR, A, JUPITER FL 33469-5530		Closed-Certificate Issued	CHESTER	INSTALL 2 ACCORDION SHUTTERS TO ENCLOSE PATIO		
08/08/2019	BLD2019080368	Residential Garage Door Replacement	10 SE TURTLE CREEK DR, TEQUESTA FL 33469-5530		Closed-Certificate Issued	HEATLEY	REMOVE AND REPLACE 2 - 9 X 7 GARAGE DOORS NO SIZE CHANGE		
11/07/2018	BLD2018110247	Residential Shutters	10 SE TURTLE CREEK DR, TEQUESTA FL 33469-5530		Closed-Certificate Issued	HEATLEY	Installation of 16 Accordion Hurricane Shutters		
10/10/2017	BPL2017100968	Residential Trade Plumbing	10 SE TURTLE CREEK DR, TEQUESTA FL 33469-5530		DONE		ABANDON SEPTIC AND RUN 120 FT OF NEW 4" PVC PVC SEWER LINE FROM HOUSE TO TAP.		T204418
04/27/2017	BAC2017050785	Heating-A/C- Refrig Residential Changeout	10 SE TURTLE CREEK DR, B, JUPITER FL 33469-1533		DONE		REPLACE A/C UNIT WITHOUT DUCT REPLACEMENT FOR RESIDENTIAL BUILDING		T197077
03/04/2016	BSHU2016030503	Residential Shutters	10 SE TURTLE CREEK DR, D, JUPITER FL 33469-1533		DONE		install 6 openings of accordion shutters		T179676
07/17/2015	BACC2015070791	Heating-A/C- Refrig- Commercial Changeout	10 SE TURTLE CREEK DR, D, JUPITER FL 33469-1533		DONE		INSTALL NEW A/C UNIT WITHOUT DUCT REPLACEMENT FOR COMMERCIAL BUILDING.		T171363
05/15/2015	BACC2015050481	Heating-A/C- Refrig- Commercial Changeout	10 SE TURTLE CREEK DR, E, JUPITER FL 33469-5530		DONE		PERMIT RENEWED 12-29- 15 (6 MONTHS) REPLACE A/C UNIT WITHOUT DUCT REPLACEMENT FOR RESIDENTIAL BUILDING		T168853
07/26/2010	BALA2010070658	Residential Low Voltage	10 SE TURTLE CREEK DR, TEQUESTA FL 33469-5530		DONE		Install alarm, one master, 3 devices		T118984
08/06/2008	BRR2008080389	Residential Roofing	10 SE TURTLE CREEK DR, B, JUPITER FL 33469-1533		DONE	TURTLE CREEK	RE ROOF TILE & FLAT- BUILDING 10- COMMERCIAL		T106000

## Martin County Florida Your County. Your Community.

2401 SE Monterey Road, Stuart, FL 34996

Phone (772) 288-5400





**Front Elevation** 



**Rear Elevation** 



8d Nails



**Right Elevation** 



Left Elevation



19/32" Sheathing





6" Max Spacing



6" Max Spacing



6" Max Spacing



Single Wrap



Single Wrap



Truss 24" O.C.





**Building 10**