





Benchmark Inspections, Inc. P.O. Box 1523 Hobe Sound, FL 33475 Phone: 888-984-4484

E-mail:cplaia@benchmarkinspectionpros.com

Wind Mitigation

Turtle Creek Association #1 Inc. 6 SE Concourse Dr Tequesta, FL 33469 October 10, 2023

Report Summary:

1. Building Code: C. Built 1971

2. Roof Covering: A. All roof coverings listed meet FBC Product Approval

3. Roof Deck Attchment: C. 8d nail 6" Max Spacing

4. Roof to Wall Attachment: B. Clips

5. Roof Geometry: A. Hip Roof

6. SWR: **B. No SWR**

7. Opening Protection Credit: X.

8. Construction Type: 100% Concrete/Masonry - 0% Wood Frame - 0% Other

NOTICE: This Report is in accordance with the CLIENT AGREEMENT, and is subject to the terms and conditions agreed upon therein. Upon receiving this report, Client agrees that it has been read in its entirety. Our inspection and this report have been performed with a written client agreement that limits its scope and usefulness. Unauthorized recipients are therefore advised not to rely upon this report, but rather to retain the services of an appropriately qualified home inspector of their choice to provide them with their own evaluation and report. Please note that the wall construction type in the report is an estimate and is included as a courtesy to your insurance agent or carrier which is classified between masonry/concrete, wood frame and/or other wall construction types.

Uniform Mitigation Verification Inspection Form

Maintain a copy of this form and any documentation provided with the insurance policy

Inspect	ion Date: October 10, 2023						
Owner	Information						
Owner	Name: Turtle Creek Associatio	n #1 Inc.		Contact Person:			
Addres	s: 6 SE Concourse Dr			Home Phone:			
City: Te	equesta	Zip: 33469		Work Phone:			
County	: Martin			Cell Phone:			
Insuran	ce Company:			Policy #:			
Year of	Home: 1971	# of Stories: 2		Email:			
accomp	Any documentation used in voany this form. At least one ph 7. The insurer may ask additi	otograph must accomp	any this form to valida	ate each attribute marked	l in questions 3		
the	Iding Code: Was the structure b	counties), South Florida	Building Code (SFBC	-94)?			
Ш	A. Built in compliance with the a date after 3/1/2002: Building F			n 2002/2003 provide a peri	nit application with		
	B. For the HVHZ Only: Built in provide a permit application wit	compliance with the SFI	BC-94: Year Built	For homes built in 19 tition Date (MM/DD/YYYY)	94, 1995, and 1996		
\times	C. Unknown or does not meet th						
OR	of Covering: Select all roof cove Year of Original Installation/Repering identified.						
		ermit Application Date	FBC or MDC Product Approval #	Year of Original Installation or Replacement	No Information Provided for Compliance		
	1. Asphalt/Fiberglass Shingle						
	■ 2. Concrete/Clay Tile	08/06/08	2008080379	2008			
	3. Metal				$\overline{\Box}$		
	4. Built Up						
	-	08/06/08	2008080379	2008			
	6. Other	<u> </u>					
				1			
\times	A. All roof coverings listed above installation OR have a roofing p						
	B. All roof coverings have a Mia	ami-Dade Product Appro	val listing current at tin	ne of installation OR (for the	ne HVHZ only) a		
	roofing permit application after		·	_	iter.		
片	C. One or more roof coverings d	•		Б.			
Ш	D. No roof coverings meet the re						
3. Roc	of Deck Attachment: What is the	·					
	A. Plywood/Oriented strand boa by staples or 6d nails spaced at shinglesOR- Any system of so mean uplift less than that require	6" along the edge and 1 rews, nails, adhesives, o	2" in the fieldOR- B ther deck fastening syst	atten decking supporting v	vood shakes or wood		
	B. Plywood/OSB roof sheathing 24"inches o.c.) by 8d common rother deck fastening system or to	g with a minimum thickn nails spaced a maximum russ/rafter spacing that is	ess of 7/16" inch attache of 12" inches in the fie shown to have an equi	ldOR- Any system of screvalent or greater resistance	ews, nails, adhesives,		
	a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf. C. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 6" inches in the fieldOR- Dimensional lumber/Tongue & Groove decking with a minimum of 2 nails per board (or 1 nail per board if each board is equal to or less than 6 inches in width)OR- Inspectors Initials CP Property Address 6 SE Concourse Tequesta, FL 33469						
msheet	ors initials roperty Au	ui cos	1, 1 2 00 100				

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at least 182 psf.
D. Reinforced Concrete Roof Deck.
E. Other:
F. Unknown or unidentified.
G. No attic access.
4. Roof to Wall Attachment: What is the WEAKEST roof to wall connection? (Do not include attachment of hip/valley jacks within 5 feet of the inside or outside corner of the roof in determination of WEAKEST type)
A. Toe Nails
Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or
Metal connectors that do not meet the minimal conditions or requirements of B, C, or D
Minimal conditions to qualify for categories B, C, or D. All visible metal connectors are:
Secured to truss/rafter with a minimum of three (3) nails, and
Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion.
☑ B. Clips
Metal connectors that do not wrap over the top of the truss/rafter, or
Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails.
C. Single Wraps Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side.
D. Double Wraps
Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or
Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side.
 E. Structural Anchor bolts structurally connected or reinforced concrete roof. F. Other:
G. Unknown or unidentified
H. No attic access
5. Roof Geometry: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification).
A. Hip Roof Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: 0 feet; Total roof system perimeter: 425 feet
B. Flat Roof Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft
C. Other Roof Any roof that does not qualify as either (A) or (B) above.
 6. Secondary Water Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss. B. No SWR. C. Unknown or undetermined.
Inspectors Initials CP Property Address 6 SE Concourse Tequesta, FL 33469
*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

7. Opening Protection: What is the weakest form of wind borne debris protection installed on the structure? First, use the table to determine the weakest form of protection for each category of opening. Second, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings and (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable. Non-Glazed **Opening Protection Level Chart Glazed Openings Openings** Place an "X" in each row to identify all forms of protection in use for each Windows opening type. Check only one answer below (A thru X), based on the weakest Garage Glass Entry Garage or Entry Skylights form of protection (lowest row) for any of the Glazed openings and indicate **Doors Block** Doors **Doors** Doors the weakest form of protection (lowest row) for Non-Glazed openings. Not Applicable- there are no openings of this type on the structure Α Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights) В Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights) С Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007 Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E D 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance Opening Protection products that appear to be A or B but are not verified Ν Other protective coverings that cannot be identified as A, B, or C No Windborne Debris Protection Х A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level A in the table above). Miami-Dade County PA 201, 202, and 203 Florida Building Code Testing Application Standard (TAS) 201, 202, and 203 American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996 Southern Standards Technical Document (SSTD) 12 For Skylights Only: ASTM E 1886 and ASTM E 1996 For Garage Doors Only: ANSI/DASMA 115 A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist LA.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or X in the table above A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All Glazed openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level B in the table above): ASTM E 1886 and ASTM E 1996 (Large Missile - 4.5 lb.) SSTD 12 (Large Missile – 4 lb. to 8 lb.) For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large Missile - 2 to 4.5 lb.) ☐ B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above L C. Exterior Opening Protection- Wood Structural Panels meeting FBC 2007 All Glazed openings are covered with plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above). LC.1 All Non-Glazed openings classified as A, B, or C in the table above, or no Non-Glazed openings exist LC.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in the table above C.3 One or More Non-Glazed openings is classified as Level N or X in the table above Inspectors Initials CP Property Address 6 SE Concourse Tequesta, FL 33469

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

N. Exterior Opening Protection (unverified shutter sprotective coverings not meeting the requirements of An with no documentation of compliance (Level N in the ta	nswer "A", "B", or C" or systems that	
N.1 All Non-Glazed openings classified as Level A, B, C, o	<i>'</i>	Lonenings evist
N.2 One or More Non-Glazed openings classified as Level table above		
N.3 One or More Non-Glazed openings is classified as Leve	el X in the table above	
X. None or Some Glazed Openings One or more Glazed	ed openings classified and Level X in	1 the table above.
MITIGATION INSPECTIONS MUST B Section 627.711(2), Florida Statutes, provi	~	
Qualified Inspector Name: CHARLIE PLAIA	License Type: HOME INSPECTOR	License or Certificate #: HI 4860
Inspection Company: BENCHMARK INSPECTIONS, INC	Phone: 88	38-984-4484
Qualified Inspector – I hold an active license as a	: (check one)	
Home inspector licensed under Section 468.8314, Florida Statute training approved by the Construction Industry Licensing Board	es who has completed the statutory numb and completion of a proficiency exam.	er of hours of hurricane mitigation
Building code inspector certified under Section 468.607, Florida		
General, building or residential contractor licensed under Section		
Professional engineer licensed under Section 471.015, Florida St		
Professional architect licensed under Section 481.213, Florida St		
Any other individual or entity recognized by the insurer as posse verification form pursuant to Section 627.711(2), Florida Statute		perly complete a uniform mitigation
(print name) contractors and professional engineers only) I had my emploand I agree to be responsible for his/her work. Qualified Inspector Signature: An individual or entity who knowingly or through gross nesubject to investigation by the Florida Division of Insurance appropriate licensing agency or to criminal prosecution. (S	ructures personally and not througect employee who possesses the recond I personally performed the inspoyee () per (print name of inspector) Date: 10/10/2023 gligence provides a false or frauduee Fraud and may be subject to admection 627.711(4)-(7), Florida Statu	th employees or other persons. quisite skill, knowledge, and pection or (licensed form the inspection lent mitigation verification form is ninistrative action by the utes) The Qualified Inspector who
certifies this form shall be directly liable for the misconduc performed the inspection.	t of employees as if the authorized	mitigation inspector personally
<u>Homeowner to complete</u> : I certify that the named Qualified residence identified on this form and that proof of identification		
Signature:I	Date: 10/10/2023	
		
An individual or entity who knowingly provides or utters a obtain or receive a discount on an insurance premium to w of the first degree. (Section 627.711(7), Florida Statutes)		
The definitions on this form are for inspection purposes on as offering protection from hurricanes.	ly and cannot be used to certify an	y product or construction feature
Inspectors Initials CP Property Address 6 SE Concours	e Tequesta, FL 33469	
*This verification form is valid for up to five (5) years prov	ided no material changes have bee	n made to the structure or

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155

Page 4 of 4

Click any of the results below to view more details.

Showing 1-10 of 15 | Download results

<u>Application</u> <u>Date</u>	Record Number	Record Type	<u>Address</u>	Action	<u>Status</u>	<u>Project</u> <u>Name</u>	<u>Description</u>	Expiration Date	Kiva Hist T #
08/11/2023	BLD2023080591	Heating-A/C- Refrig Residential Changeout	6 SE CONCOURSE DR, C, JUPITER FL 33469		Closed-Cancelled	ANGELINA COTRONEO	A/C CHANGE OUT WITH NEW DISCONNECT BOX		
08/11/2023	BLD2023080593	Heating-A/C- Refrig- Commercial Changeout	6 SE CONCOURSE DR, C, JUPITER FL 33469		Closed-Certificate Issued	ANGELINA COTRONEO	A/C CHANGE OUT WITH NEW DISCONNECT BOX		
06/19/2023	BLD2023061100	Commercial Replacement Windows/Doors	6 SE CONCOURSE DR, D, JUPITER FL 33469		Closed-Certificate Issued	Minea, Bruce	Replacing on existing openings 7 Impact Windows		
07/09/2021	BLD2021070528	Commercial Replacement Windows/Doors	6 SE Concourse DR, E, JUPITER FL 33469-1554		Closed-Certificate Issued		Replace 5 windows size for size with impact		
04/15/2021	BLD2021041023	Heating-A/C- Refrig Residential Changeout	6 SE CONCOURSE DR, D, JUPITER FL 33469-5502		Closed-Certificate Issued		PERMIT RENEWED 11-17- 21 (6 MONTHS) REPLACE A/C EQUIPMENT LIKE FOR LIKE CHANGE OUT		
06/24/2015	BMIC2015070825	Commercial Miscellaneous	6 SE TURTLE CREEK DR, E, JUPITER FL 33469-1554		DONE		cut asphalt drive back 12 inches and pour flat concrets curbing to stop asphalt erosin at grass line		T170457
12/12/2014	BACC2015020848	Heating-A/C- Refrig- Commercial Changeout	6 SE CONCOURSE DR, A, JUPITER FL 33469-1539		DONE		REPLACE A/C UNIT WITHOUT DUCT REPLACEMENT FOR RESIDENTIAL BUILDING		T163507
12/09/2014	BAC2015020179	Heating-A/C- Refrig Residential Changeout	6 SE CONCOURSE DR, C, JUPITER		DONF		replace existing system with Irane		T163387
08/06/2008	BRR2008080379	Residential Roofing	FL 33469-5502 6 SE CONCOURSE DR, A, JUPITER FL 33469-1539		DONE	TURTLE CREEK	RE ROOF TILE & FLAT- BUILDING 6- COMMERCIAL		T105990
05/16/2007	BSHU2007050434	Residential Shutters	6 SE CONCOURSE DR, D, JUPITER FL 33469-5502		DONE		INSTALL 4 ACCORDIAN SHUTTERS		T96071

Martin County Florida Your County. Your Community.

2401 SE Monterey Road, Stuart, FL 34996

Phone (772) 288-5400





Front Elevation



Rear Elevation



8d Nails



Right Elevation



Left Elevation



19/32" Sheathing





6" Max Spacing



6" Max Spacing



6" Max Spacing



Clip



Clip



Truss 24" O.C.





Building 6



200	
	v v
Impact rated hurricane panels.	Glazed openings protected.
mpaot ration framework	orazoa oporringo protoctoa.
30	34
	(3)
	v v
	44,
	49
Impact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
Impact rated hurricane panels.	Glazed openings protected.
Impact rated hurricane panels.	Glazed openings protected.
Impact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.



*	
20	No.
mpact rated hurricane panels.	Glazed openings protected.
	No.
, asia	
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.



200	
	v v
Impact rated hurricane panels.	Glazed openings protected.
mpaot ration framework	orazoa oporringo protoctoa.
30	34
	(3)
	v v
	44,
	49
Impact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
Impact rated hurricane panels.	Glazed openings protected.
Impact rated hurricane panels.	Glazed openings protected.
Impact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.
mpact rated hurricane panels.	Glazed openings protected.



40.00	46.
20	
20	
mpact rated hurricane panels.	Glazed openings protected.
*	
the state of the s	
7 P F 25 1	
mpact rated hurricane panels.	Glazed openings protected.
input rated framedine pariolo.	Giazoa opoimigo protoctoa.

