





Benchmark Inspections, Inc. P.O. Box 1523 Hobe Sound, FL 33475 Phone: 888-984-4484

E-mail:cplaia@benchmarkinspectionpros.com

Wind Mitigation

Turtle Creek Association #1 Inc. 4 SE Turtle Creek Dr Tequesta, FL 33469 October 10, 2023

Report Summary:

1. Building Code: C. Built 1971

2. Roof Covering: A. All roof coverings listed meet FBC Product Approval

3. Roof Deck Attchment: C. 8d nail 6" Max Spacing

4. Roof to Wall Attachment: B. Clips

5. Roof Geometry: A. Hip Roof

6. SWR: **B. No SWR**

7. Opening Protection Credit: X.

8. Construction Type: 100% Concrete/Masonry - 0% Wood Frame - 0% Other

NOTICE: This Report is in accordance with the CLIENT AGREEMENT, and is subject to the terms and conditions agreed upon therein. Upon receiving this report, Client agrees that it has been read in its entirety. Our inspection and this report have been performed with a written client agreement that limits its scope and usefulness. Unauthorized recipients are therefore advised not to rely upon this report, but rather to retain the services of an appropriately qualified home inspector of their choice to provide them with their own evaluation and report. Please note that the wall construction type in the report is an estimate and is included as a courtesy to your insurance agent or carrier which is classified between masonry/concrete, wood frame and/or other wall construction types.

Uniform Mitigation Verification Inspection Form

Maintain a copy of this form and any documentation provided with the insurance policy

Inspection Date: October 10, 2023							
Owner Information							
Owner Name: Turtle Creek Association #1	Inc.		Contact Person:				
Address: 4 SE Turtle Creek Dr			Home Phone:				
City:Tequesta	Zip: 33469		Work Phone:				
County: Martin			Cell Phone:				
Insurance Company:			Policy #:				
Year of Home: 1971	# of Stories: 2		Email:				
NOTE: Any documentation used in valid accompany this form. At least one photog though 7. The insurer may ask additional	graph must accompa	ny this form to validat	e each attribute marked				
1. <u>Building Code</u> : Was the structure built the HVHZ (Miami-Dade or Broward cou	inties), South Florida	Building Code (SFBC-9	4)?				
A. Built in compliance with the FBC a date after 3/1/2002: Building Perm			2002/2003 provide a perm	nit application with			
B. For the HVHZ Only: Built in comprovide a permit application with a d	pliance with the SFB	C-94: Year Built		94, 1995, and 1996			
X C. Unknown or does not meet the red							
2. <u>Roof Covering:</u> Select all roof covering OR Year of Original Installation/Replace covering identified.							
Permit A	Application Date	FBC or MDC Product Approval #	Year of Original Installation or Replacement	No Information Provided for Compliance			
1. Asphalt/Fiberglass Shingle /							
2. Concrete/Clay Tile 08/0	06/08	2008080374	2008				
3. Metal /							
4. Built Up				$\overline{\Box}$			
	06/08	2008080374	2008	ī			
6. Other				Ä			
A. All roof coverings listed above meet the FBC with a FBC or Miami-Dade Product Approval listing current at time of installation OR have a roofing permit application date on or after 3/1/02 OR the roof is original and built in 2004 or later. B. All roof coverings have a Miami-Dade Product Approval listing current at time of installation OR (for the HVHZ only) a roofing permit application after 9/1/1994 and before 3/1/2002 OR the roof is original and built in 1997 or later.							
C. One or more roof coverings do no	ot meet the requiremen	its of Answer "A" or "B	".				
D. No roof coverings meet the require	rements of Answer "A	" or "B".					
3. Roof Deck Attachment : What is the we	akest form of roof dec	ck attachment?					
A. Plywood/Oriented strand board (6 by staples or 6d nails spaced at 6" a shinglesOR- Any system of screw mean uplift less than that required fo B. Plywood/OSB roof sheathing wit 24"inches o.c.) by 8d common nails other deck fastening system or truss/a maximum of 12 inches in the field	OSB) roof sheathing a along the edge and 12 s, nails, adhesives, other or Options B or C below th a minimum thickness spaced a maximum of frafter spacing that is s	ttached to the roof truss "in the fieldOR- Bat her deck fastening system w. ss of 7/16"inch attached f 12" inches in the field shown to have an equiva	ten decking supporting w m or truss/rafter spacing th to the roof truss/rafter (sp. -OR- Any system of scre- alent or greater resistance	ood shakes or wood nat has an equivalent baced a maximum of ws, nails, adhesives,			
C. Plywood/OSB roof sheathing with 24"inches o.c.) by 8d common nails decking with a minimum of 2 nails paragraph of the state of the s	th a minimum thickness spaced a maximum oper board (or 1 nail pe	ss of 7/16"inch attached if 6" inches in the field. board if each board is	to the roof truss/rafter (sp-OR- Dimensional lumber equal to or less than 6 inc	er/Tongue & Groove			

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

		of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent istance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at least
	D. Reinforce	ed Concrete Roof Deck.
닏		or unidentified.
Ш	G. No attic a	access.
	eet of the insid	tachment: What is the <u>WEAKEST</u> roof to wall connection? (Do not include attachment of hip/valley jacks within e or outside corner of the roof in determination of WEAKEST type)
Ш	A. Toe Nails	
	Ц	Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or
		Metal connectors that do not meet the minimal conditions or requirements of B, C, or D
Mi	nimal condition	ons to qualify for categories B, C, or D. All visible metal connectors are:
	\boxtimes	Secured to truss/rafter with a minimum of three (3) nails, and
	\boxtimes	Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion.
\times	B. Clips	
		Metal connectors that do not wrap over the top of the truss/rafter, or
	\boxtimes	Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails.
	C. Single W	•
		Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side.
	D. Double V	Vraps
		Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or
		Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side.
	E. Structural	Anchor bolts structurally connected or reinforced concrete roof.
	F. Other:	
	G. Unknown	or unidentified
	H. No attic a	ccess
		What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification).
\times	A. Hip Roof	
	B. Flat Roof	Total length of non-hip features: 0 feet; Total roof system perimeter: 425 feet Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of
		less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft
Ш	C. Other Ro	of Any roof that does not qualify as either (A) or (B) above.
6. <u>Se</u>	A. SWR (also sheathing dwelling B. No SWR.	r Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) to called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the from water intrusion in the event of roof covering loss.
Inspe	ctors Initials	CP_Property Address_4 SE Turtle Creek Dr Tequesta, FL 33469
^ I nis	verification fo	orm is valid for up to five (5) years provided no material changes have been made to the structure or

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

7. Opening Protection: What is the weakest form of wind borne debris protection installed on the structure? First, use the table to determine the weakest form of protection for each category of opening. Second, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings and (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable. Non-Glazed **Opening Protection Level Chart Glazed Openings Openings** Place an "X" in each row to identify all forms of protection in use for each Windows opening type. Check only one answer below (A thru X), based on the weakest Garage Glass Entry Garage or Entry Skylights form of protection (lowest row) for any of the Glazed openings and indicate **Doors Block** Doors **Doors** Doors the weakest form of protection (lowest row) for Non-Glazed openings. Not Applicable- there are no openings of this type on the structure Α Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights) В Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights) С Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007 Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E D 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance Opening Protection products that appear to be A or B but are not verified Ν Other protective coverings that cannot be identified as A, B, or C No Windborne Debris Protection Х A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level A in the table above). Miami-Dade County PA 201, 202, and 203 Florida Building Code Testing Application Standard (TAS) 201, 202, and 203 American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996 Southern Standards Technical Document (SSTD) 12 For Skylights Only: ASTM E 1886 and ASTM E 1996 For Garage Doors Only: ANSI/DASMA 115 A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist LA.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or X in the table above A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All Glazed openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level B in the table above): ASTM E 1886 and ASTM E 1996 (Large Missile - 4.5 lb.) SSTD 12 (Large Missile – 4 lb. to 8 lb.) For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large Missile - 2 to 4.5 lb.) ☐ B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above L C. Exterior Opening Protection- Wood Structural Panels meeting FBC 2007 All Glazed openings are covered with plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above). LC.1 All Non-Glazed openings classified as A, B, or C in the table above, or no Non-Glazed openings exist LC.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in the table above C.3 One or More Non-Glazed openings is classified as Level N or X in the table above Inspectors Initials CP Property Address 4 SE Turtle Creek Dr Tequesta, FL 33469

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

N. Exterior Opening Protection (unverified shutter sprotective coverings not meeting the requirements of Arwith no documentation of compliance (Level N in the ta	nswer "A", "B", or C" or sy	
N.1 All Non-Glazed openings classified as Level A, B, C, o	·	on-Glazed openings exist
N.2 One or More Non-Glazed openings classified as Level label above	D in the table above, and no No	on-Glazed openings classified as Level X in the
N.3 One or More Non-Glazed openings is classified as Leve	el X in the table above	
X. None or Some Glazed Openings One or more Glaze	ed openings classified and L	evel X in the table above.
MITIGATION INSPECTIONS MUST B Section 627.711(2), Florida Statutes, provi	~	
Qualified Inspector Name: CHARLIE PLAIA	License Type: HOME INSPECTOR	License or Certificate #: HI 4860
Inspection Company: BENCHMARK INSPECTIONS, INC	I	Phone: 888-984-4484
Qualified Inspector – I hold an active license as a	: (check one)	
Home inspector licensed under Section 468.8314, Florida Statute training approved by the Construction Industry Licensing Board Building code inspector certified under Section 468.607, Florida General, building or residential contractor licensed under Section Professional engineer licensed under Section 471.015, Florida St Professional architect licensed under Section 481.213, Florida St Any other individual or entity recognized by the insurer as posses	es who has completed the statur and completion of a proficienc Statutes. a 489.111, Florida Statutes. atutes. atutes. ssing the necessary qualification	y exam.
verification form pursuant to Section 627.711(2), Florida Statute: Individuals other than licensed contractors licensed under 3		
under Section 471.015, Florida Statues, must inspect the str <u>Licensees under s.471.015 or s.489.111 may authorize a dire</u> <u>experience to conduct a mitigation verification inspection.</u>	cuctures personally and no ect employee who possesse and I personally performed	through employees or other persons. sthe requisite skill, knowledge, and the inspection or (licensed perform the inspection ctor)
An individual or entity who knowingly or through gross ne subject to investigation by the Florida Division of Insurance		
appropriate licensing agency or to criminal prosecution. (See	ection 627.711(4)-(7), Flor	ida Statutes) The Qualified Inspector who
certifies this form shall be directly liable for the misconduc performed the inspection.	t of employees as if the au	thorized mitigation inspector personally
Homeowner to complete: I certify that the named Qualified residence identified on this form and that proof of identification Signature:	n was provided to me or my	
An individual or entity who knowingly provides or utters a obtain or receive a discount on an insurance premium to w of the first degree. (Section 627.711(7), Florida Statutes)		
The definitions on this form are for inspection purposes on as offering protection from hurricanes.	ly and cannot be used to co	ertify any product or construction feature
Inspectors Initials CP Property Address 4 SE Turtle Cre	ek Dr Tequesta, FL 3346	9
*This verification form is valid for up to five (5) years provinaccuracies found on the form.	ided no material changes	have been made to the structure or

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155

Click any of the results below to view more details.

Showing 11-20 of 22 | Download results

_	<u>Application</u>	Record					<u>Project</u>		<u>Expiration</u>	Kiva Hi
	Date	Number	Record Type	<u>Address</u>	Action	<u>Status</u>	Name	<u>Description</u>	Date	<u>T#</u>
	10/13/2011	BAC2011100340	Heating-A/C-Refrig Residential Changeout	4 SE TURTLE CREEK DR, B, JUPITER FL 33469-1537		DONE		ac change out		T130207
	09/14/2010	BREP2010090324	Residential Replacement Windows/Doors	4 SE TURTLE CREEK DR, TEQUESTA FL 33469-1587		DONE		REPLACE (2) EXISTING GARAGE DOOR WITH DADE COUNTY CODE IMPACT RATED GARAGE DOOR **NO SIZE CHANGE		T120222
	09/16/2009	BSHU2009090228	Residential Shutters	4 SE TURTLE CREEK DR, D, JUPITER FL 33469-1537		DONE		INSTALL 2 ACCODION SHUTTTERS ON PATIO		T112701
	07/16/2009	BSHU2009070253	Residential Shutters	4 SE TURTLE CREEK DR, C, JUPITER FL		DONE		INSTALL 8 ACCORDION SHUTTERS		T111714
	08/06/2008	BRR2008080374	Residential Roofing	33469-1537 4 SE TURTLE CREEK DR, D, JUPITER FL 33469-1537		DONE	TURTLE CREEK	RE ROOF TILE & FLAT- COMMERCIAL- BUILDING 4		T105987
	10/17/2006	BPL2006100474	Residential Trade Plumbing	4 SE TURTLE CREEK DR, TEQUESTA FL		DONE		SEWER TIE IN		T90815
	06/16/2003	BDR2003060470	Residential Driveway	33469-1587 4 SE TURTLE CREEK DR, TEQUESTA FL 33469-1587		DONE		PERMIT RENEWED ON 04-22-13. Install a paving brick drive, walk, and front proch		
	12/13/2002	BMIC2003010118	Commercial Miscellaneous	4 SE TURTLE CREEK DR, B, JUPITER FL 33469-1537		DONE		CONCRETE RESTORATION ON BLDG#4 APTS F,E,B&D		T36952
	06/17/2002	BRX12002060370	Residential Roofing Repair	4 SE TURTLE CREEK DR, TEQUESTA FL 33469-1587		DONE				
	02/03/1998	BRR98020251	Residential Roofing	4 SE TURTLE CREEK DR, C, JUPITER FL 33469-1537		DONE				

Martin County Florida Your County. Your Community.

2401 SE Monterey Road, Stuart, FL 34996

Phone (772) 288-5400





Front Elevation



Rear Elevation



8d Nails



Right Elevation



Left Elevation



19/32" Sheathing






6" Max Spacing



6" Max Spacing



6" Max Spacing



Clip



Clip



Truss 24" O.C.





Building 4