





Benchmark Inspections, Inc. P.O. Box 1523 Hobe Sound, FL 33475 Phone: 888-984-4484

E-mail:cplaia@benchmarkinspectionpros.com

Wind Mitigation

Turtle Creek Association #1 Inc. 2 SE Turtle Creek Dr Tequesta, FL 33469 October 10, 2023

Report Summary:

1. Building Code: C. Built 1971

2. Roof Covering: A. All roof coverings listed meet FBC Product Approval

3. Roof Deck Attchment: C. 8d nail 6" Max Spacing

4. Roof to Wall Attachment: B. Clips

5. Roof Geometry: A. Hip Roof

6. SWR: **B. No SWR**

7. Opening Protection Credit: X.

8. Construction Type: 100% Concrete/Masonry - 0% Wood Frame - 0% Other

NOTICE: This Report is in accordance with the CLIENT AGREEMENT, and is subject to the terms and conditions agreed upon therein. Upon receiving this report, Client agrees that it has been read in its entirety. Our inspection and this report have been performed with a written client agreement that limits its scope and usefulness. Unauthorized recipients are therefore advised not to rely upon this report, but rather to retain the services of an appropriately qualified home inspector of their choice to provide them with their own evaluation and report. Please note that the wall construction type in the report is an estimate and is included as a courtesy to your insurance agent or carrier which is classified between masonry/concrete, wood frame and/or other wall construction types.

Uniform Mitigation Verification Inspection Form

Maintain a copy of this form and any documentation provided with the insurance policy

Inspect	tion Date: October 10, 2023	of this form and any c	F		<u> </u>		
Owner	· Information						
Owner	Name: Turtle Creek Association	n #1 Inc.		Contact Person:			
Addres	s: 2 SE Turtle Creek Dr			Home Phone:			
City: To	equesta	Zip: 33469	Zip: 33469		Work Phone:		
County	: Martin				Cell Phone:		
Insurar	nce Company:			Policy #:			
Year o	f Home: 1971	# of Stories: 2		Email:			
accom	: Any documentation used in v pany this form. At least one ph 17. The insurer may ask addit	otograph must accomp	any this form to valida	ate each attribute marke	d in questions 3		
	ilding Code: Was the structure be HVHZ (Miami-Dade or Broward A. Built in compliance with the	l counties), South Florida	a Building Code (SFBC	-94)?			
Ш	a date after 3/1/2002: Building 1	Permit Application Date (MM/DD/YYYY)	11 2002/2003 provide a per	ппі аррпсацоп міш		
	B. For the HVHZ Only: Built in provide a permit application with	compliance with the SFI h a date after 9/1/1994: F	BC-94: Year Built Building Permit Applica	For homes built in 19 tion Date (MM/DD/YYYY)	994, 1995, and 1996		
\times	C. Unknown or does not meet the	ne requirements of Answe	er "A" or "B"				
OR	of Covering: Select all roof covering: Year of Original Installation/Regring identified.						
		Permit Application Date	FBC or MDC Product Approval #	Year of Original Installation or Replacement	No Information Provided for Compliance		
	1. Asphalt/Fiberglass Shingle						
	2. Concrete/Clay Tile	03/21/08	2008030612	2008			
	3. Metal						
	4. Built Up						
	★ 5. Membrane	03/21/08	2008030612	2008			
	6. Other						
■□□□2Beautiful (a)	A. All roof coverings listed about installation OR have a roofing proofing proofing permit application after C. One or more roof coverings on D. No roof coverings meet the roof Dark Attachment, What is the	ermit application date on ami-Dade Product Appro 9/1/1994 and before 3/1/2 do not meet the requirement equirements of Answer "	or after 3/1/02 OR the eval listing current at tin 2002 OR the roof is origents of Answer "A" or "A" or "B".	roof is original and built in ne of installation OR (for t ginal and built in 1997 or	n 2004 or later. he HVHZ only) a		
3. <u>Ro</u>	of Deck Attachment: What is the			as rofter (anoard a maxim	um of 24" inches o a)		
	A. Plywood/Oriented strand box by staples or 6d nails spaced at shinglesOR- Any system of se mean uplift less than that requir	6" along the edge and 1 crews, nails, adhesives, or ed for Options B or C bel	2" in the fieldOR- B ther deck fastening syst low.	atten decking supporting tem or truss/rafter spacing	wood shakes or wood that has an equivalent		
	B. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum 24"inches o.c.) by 8d common nails spaced a maximum of 12" inches in the fieldOR- Any system of screws, nails, adhese other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d nails sp a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf.						
\boxtimes	C. Plywood/OSB roof sheathin 24"inches o.c.) by 8d common decking with a minimum of 2 n	nails spaced a maximum ails per board (or 1 nail p	of 6" inches in the fiel per board if each board	dOR- Dimensional lumb is equal to or less than 6 i	per/Tongue & Groove		
Inspec	tors Initials <u>CP</u> Property Ad	dress 2 SE Turtle Cree	ek Dr Tequesta, FL 33	3469			

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

			of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent sistance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at least
		-	ed Concrete Roof Deck.
		E. Other:	
		F. Unknown	or unidentified.
		G. No attic a	access.
4.		eet of the insid	tachment: What is the <u>WEAKEST</u> roof to wall connection? (Do not include attachment of hip/valley jacks within e or outside corner of the roof in determination of WEAKEST type)
	Ш	A. Toe Nails	
			Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or
			Metal connectors that do not meet the minimal conditions or requirements of B, C, or D
	Mir	nimal conditio	ons to qualify for categories B, C, or D. All visible metal connectors are:
		\boxtimes	Secured to truss/rafter with a minimum of three (3) nails, and
		\boxtimes	Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion.
	\times	B. Clips	
			Metal connectors that do not wrap over the top of the truss/rafter, or
		\boxtimes	Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails.
		C. Single W	Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side.
	П	D. Double V	
	_		Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or
			Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side.
		E. Structural F. Other:	•
	Ħ		n or unidentified
		H. No attic a	
5.			What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification).
	\boxtimes	A. Hip Roof	Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: 0 feet; Total roof system perimeter: 425 feet
		B. Flat Roof	• • • • • • • • • • • • • • • • • • • •
		C. Other Roo	
6.	Sec	A. SWR (also sheathing dwelling) B. No SWR.	er Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) so called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the from water intrusion in the event of roof covering loss.
In	spec	tors Initials _	CP Property Address 2 SE Turtle Creek Dr Tequesta, FL 33469
*T	'his v	verification fo	orm is valid for up to five (5) years provided no material changes have been made to the structure or
		· · · · · · · · · · · · · · · · · · ·	

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

7. Opening Protection: What is the weakest form of wind borne debris protection installed on the structure? First, use the table to determine the weakest form of protection for each category of opening. Second, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings and (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable. Non-Glazed **Opening Protection Level Chart Glazed Openings Openings** Place an "X" in each row to identify all forms of protection in use for each Windows opening type. Check only one answer below (A thru X), based on the weakest Garage Glass Entry Garage or Entry Skylights form of protection (lowest row) for any of the Glazed openings and indicate **Doors Block** Doors **Doors** Doors the weakest form of protection (lowest row) for Non-Glazed openings. Not Applicable- there are no openings of this type on the structure Α Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights) В Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights) С Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007 Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E D 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance Opening Protection products that appear to be A or B but are not verified Ν Other protective coverings that cannot be identified as A, B, or C No Windborne Debris Protection Х A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level A in the table above). Miami-Dade County PA 201, 202, and 203 Florida Building Code Testing Application Standard (TAS) 201, 202, and 203 American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996 Southern Standards Technical Document (SSTD) 12 For Skylights Only: ASTM E 1886 and ASTM E 1996 For Garage Doors Only: ANSI/DASMA 115 A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist LA.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or X in the table above A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All Glazed openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level B in the table above): ASTM E 1886 and ASTM E 1996 (Large Missile - 4.5 lb.) SSTD 12 (Large Missile – 4 lb. to 8 lb.) For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large Missile - 2 to 4.5 lb.) ☐ B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above L C. Exterior Opening Protection- Wood Structural Panels meeting FBC 2007 All Glazed openings are covered with plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above). LC.1 All Non-Glazed openings classified as A, B, or C in the table above, or no Non-Glazed openings exist LC.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in the table above C.3 One or More Non-Glazed openings is classified as Level N or X in the table above Inspectors Initials CP Property Address 2 SE Turtle Creek Dr Tequesta, FL 33469

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

N. Exterior Opening Protection (unverified shutter sprotective coverings not meeting the requirements of Arwith no documentation of compliance (Level N in the talk)	nswer "A", "B", or C" or sy	
N.1 All Non-Glazed openings classified as Level A, B, C, o N.2 One or More Non-Glazed openings classified as Level I	r N in the table above, or no N	
table above N.3 One or More Non-Glazed openings is classified as Leve		1 0
X. None or Some Glazed Openings One or more Glaze	ed openings classified and L	evel X in the table above.
MITIGATION INSPECTIONS MUST B Section 627.711(2), Florida Statutes, provi	~	
Qualified Inspector Name: CHARLIE PLAIA	License Type: HOME INSPECTOR	License or Certificate #: HI 4860
Inspection Company: BENCHMARK INSPECTIONS, INC		Phone: 888-984-4484
Qualified Inspector – I hold an active license as a	: (check one)	
Home inspector licensed under Section 468.8314, Florida Statute training approved by the Construction Industry Licensing Board Building code inspector certified under Section 468.607, Florida General, building or residential contractor licensed under Section Professional engineer licensed under Section 471.015, Florida St. Professional architect licensed under Section 481.213, Florida St.	es who has completed the statut and completion of a proficienc Statutes. 489.111, Florida Statutes. atutes.	
Any other individual or entity recognized by the insurer as posses verification form pursuant to Section 627.711(2), Florida Statutes	ssing the necessary qualification	ons to properly complete a uniform mitigation
Individuals other than licensed contractors licensed under sunder Section 471.015, Florida Statues, must inspect the structure Licensees under s.471.015 or s.489.111 may authorize a direct experience to conduct a mitigation verification inspection. I, CHARLIE PLAIA am a qualified inspector a (print name) contractors and professional engineers only) I had my emploand I agree to be responsible for his/her work. Qualified Inspector Signature:	ructures personally and no ect employee who possesse nd I personally performed	through employees or other persons. sthe requisite skill, knowledge, and the inspection or (licensed perform the inspection ctor)
An individual or entity who knowingly or through gross neg subject to investigation by the Florida Division of Insurance	e Fraud and may be subje	ct to administrative action by the
appropriate licensing agency or to criminal prosecution. (Secretifies this form shall be directly liable for the misconduct performed the inspection.		
Homeowner to complete: I certify that the named Qualified residence identified on this form and that proof of identification Signature:		
An individual or entity who knowingly provides or utters a obtain or receive a discount on an insurance premium to who of the first degree. (Section 627.711(7), Florida Statutes)		
The definitions on this form are for inspection purposes onl as offering protection from hurricanes.	ly and cannot be used to co	ertify any product or construction feature
Inspectors Initials CP Property Address 2 SE Turtle Cre	ek Dr Tequesta, FL 3346	9
*This verification form is valid for up to five (5) years provinaccuracies found on the form.	ided no material changes l	have been made to the structure or

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155

Click any of the results below to view more details.

Showing 1-10 of 13 | Download results

- 1	<u>Application</u>	Record	Record Type	Address	Action	Status	<u>Project</u>	Description	<u>Expiration</u>	<u>Kiva</u>
_	<u>Date</u>	Number					<u>Name</u>	_ 30011 011011	<u>Date</u>	Hist T
	07/27/2021	BLD2021071663	Heating-A/C- Refrig Residential Changeout	2 SE TURTLE CREEK DR, E, JUPITER FL 33469-1589		Closed-Certificate Issued	RANONE	EXACT A/C CHANGE OUT, NO DUCTWORK		
	04/07/2021	BLD2021040408	Heating-A/C- Refrig Residential Changeout	2 SE TURTLE CREEK DR, F, JUPITER FL 33469-1535		Closed-Certificate Issued	AC changeout - Kolman residence	Replace old AC system with new like for like system		
	09/11/2018	BLD2018090384	Heating-A/C- Refrig Residential Changeout	2 SE TURTLE CREEK DR, TEQUESTA FL 33469-1589		Closed-Certificate Issued	STANLEY	A/C CHANGE OUT		
	08/06/2008	BRR2008080366	Residential Roofing	2 SE TURTLE CREEK DR, C, JUPITER FL 33469-1535		DONE	TURTLE CREEK	RE ROOF TILE & FLAT- BUILDING 2- COMMERCIAL		T10596
	04/11/2008	BREP2008040236	Residential Replacement Windows/Doors	2 SE TURTLE CREEK DR, TEQUESTA FL 33469-1589		DONE		change out 1- (16 x 7) garage door		T10342
	03/31/2008	BRR2008030612	Residential Roofing	2 SE TURTLE CREEK DR, TEQUESTA FL 33469-1589		DONE		MISCELLANEOUS REROOF APPLICATION:TILE OFF, SHINGLES ON. MODIFIED ON FLAT ROOF.		T10315
	04/16/2007	BSHU2007040353	Residential Shutters	2 SE TURTLE CREEK DR, E, JUPITER FL 33469-1589		DONE		Install accordion shutters on 8 openings		T95253
	12/06/2006	BPL2006120152	Residential Trade Plumbing	2 SE TURTLE CREEK DR, TEQUESTA FL 33469-1589		DONE		SEWER TIE IN		T92118
	06/30/2006	BSHU2006070761	Residential Shutters	2 SE TURTLE CREEK DR, D, JUPITER FL 33469-1535		DONE		INSTALL 1HURRICANE SHUTTER		T87703
	12/13/2002	BMIC2003010117	Commercial Miscellaneous	2 SE TURTLE CREEK DR, A, JUPITER FL 33469-1589		DONE		CONCRETE BALCONY REPAIRS ON BLDG#2 APT D,E,F		T36953

Martin County Florida Your County. Your Community.

2401 SE Monterey Road, Stuart, FL 34996

Phone (772) 288-5400





Front Elevation





Rear Elevation



Left Elevation



8d Nails



19/32" Sheathing





6" Max Spacing



6" Max Spacing



6" Max Spacing



Clip





Truss 24" O.C.





Building 2