





Benchmark Inspections, Inc. P.O. Box 1523 Hobe Sound, FL 33475 Phone: 888-984-4484

E-mail:cplaia@benchmarkinspectionpros.com

Wind Mitigation

Turtle Creek Association #1 Inc. 8 SE Turtle Creek Dr Tequesta, FL 33469 October 10, 2023

Report Summary:

1. Building Code: C. Built 1971

2. Roof Covering: A. All roof coverings listed meet FBC Product Approval

3. Roof Deck Attchment: C. 8d nail 6" Max Spacing

4. Roof to Wall Attachment: B. Clips

5. Roof Geometry: **A. Hip Roof**

6. SWR: **B. No SWR**

7. Opening Protection Credit: X.

8. Construction Type: 100% Concrete/Masonry - 0% Wood Frame - 0% Other

NOTICE: This Report is in accordance with the CLIENT AGREEMENT, and is subject to the terms and conditions agreed upon therein. Upon receiving this report, Client agrees that it has been read in its entirety. Our inspection and this report have been performed with a written client agreement that limits its scope and usefulness. Unauthorized recipients are therefore advised not to rely upon this report, but rather to retain the services of an appropriately qualified home inspector of their choice to provide them with their own evaluation and report. Please note that the wall construction type in the report is an estimate and is included as a courtesy to your insurance agent or carrier which is classified between masonry/concrete, wood frame and/or other wall construction types.

Uniform Mitigation Verification Inspection Form

Maintain a copy of this form and any documentation provided with the insurance policy

Inspecti	on Date: October 10, 2023	ans form and any a	commendation provid	ed with the msurance	, poney
	Information				
	Name: Turtle Creek Association	#1 Inc.		Contact Person:	
	: 8 SE Turtle Creek Dr	,, , , , , , , , , , , , , , , , , , , ,		Home Phone:	
City:Te		Zip: 33469		Work Phone:	
County:	·	1 00.00		Cell Phone:	
	ce Company:			Policy #:	
	Home: 1971	# of Stories: 2		Email:	
accomp	Any documentation used in valuary this form. At least one photon. The insurer may ask addition	tograph must accompa	ny this form to validate	e each attribute marked	in questions 3
the I	ding Code: Was the structure but HVHZ (Miami-Dade or Broward of A. D. Heiner Line and A.	counties), South Florida	Building Code (SFBC-9	4)?	
;	A. Built in compliance with the Flat date after 3/1/2002: Building Pe	rmit Application Date (N	MM/DD/YYYY)		
	B. For the HVHZ Only: Built in c provide a permit application with				
	C. Unknown or does not meet the			·	
OR '	f Covering: Select all roof covering Year of Original Installation/Replaced in identified.				
	Per 2.1 Roof Covering Type:	nit Application Date	FBC or MDC Product Approval #	Year of Original Installation or Replacement	No Information Provided for Compliance
	1. Asphalt/Fiberglass Shingle	<u>//</u>			
	∠ 2. Concrete/Clay Tile ∠ 2. Concrete/Clay Tile	3/06/08	2008080392	2008	
	3. Metal				
	4. Built Up				$\overline{\Box}$
		3/06/08	2008080392	2008	
	6. Other	<u>//</u>			H
_					Ш
	A. All roof coverings listed above installation OR have a roofing per B. All roof coverings have a Mian roofing permit application after 9/	mit application date on ni-Dade Product Approv 1/1994 and before 3/1/2	or after 3/1/02 OR the ro val listing current at time 002 OR the roof is origin	of is original and built in of installation OR (for th nal and built in 1997 or la	2004 or later. ne HVHZ only) a
_	C. One or more roof coverings do	=		"·	
	D. No roof coverings meet the req	uirements of Answer "A	A" or "B".		
3. Roo	f Deck Attachment: What is the	weakest form of roof de	ck attachment?		
	A. Plywood/Oriented strand board by staples or 6d nails spaced at 6 shinglesOR- Any system of scro mean uplift less than that required	" along the edge and 12 ews, nails, adhesives, of	2" in the fieldOR- Batther deck fastening system	ten decking supporting w	ood shakes or wood
	B. Plywood/OSB roof sheathing 24"inches o.c.) by 8d common na other deck fastening system or tru a maximum of 12 inches in the fie	ils spaced a maximum of ss/rafter spacing that is ld or has a mean uplift	of 12" inches in the field. shown to have an equiva- resistance of at least 103	-OR- Any system of screalent or greater resistance psf.	ews, nails, adhesives, than 8d nails spaced
	C. Plywood/OSB roof sheathing 24"inches o.c.) by 8d common na decking with a minimum of 2 nai	ils spaced a maximum o ls per board (or 1 nail p	of 6" inches in the field. er board if each board is	-OR- Dimensional lumber equal to or less than 6 in	er/Tongue & Groove
Inspect	ors Initials <u>CP</u> Property Add	ress_o o lurie Cree	k ווו requesta, FL 334	09	

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

position requirements of C or D, but is secured with a minimum of 3 nails. C. Single Wraps Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side. D. Double Wraps Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side. E. Structural Anchor bolts structurally connected or reinforced concrete roof. F. Other: G. Unknown or unidentified H. No attic access 5. Roof Geometry: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification). A. Hip Roof Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: feet; Total roof system perimeter. Total length of non-hip features: feet; Total roof system perimeter: sq ft; Total roof area has a roof slope of less than 2:12 sq ft; Total roof area has a roof slope of less than 2:12 sq ft; Total roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12 sq ft; Tot				of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent sistance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at least
F. Unknown or unidentified. G. No attic access.			-	ed Concrete Roof Deck.
G. No attic access.			E. Other:	
4. **Roof to Wall Attachment:* What is the **WEAKEST* roof to wall connection?* (Do not include attachment of hip/valley jacks within 5 lect of the inside or outside corner of the roof in determination of WEAKEST type) A. Toe Nails Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or determination of metal to moment of the plate of the wall, or determination of the comment of the plate of the wall connectors are: Secured to truss/rafter with a minimum of three (3) nails, and Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion. B. Clips Metal connectors that do not wrap over the top of the truss/rafter, and free of visible severe corrosion. Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails. C. Single Wraps Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side. D. Double Wraps Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side. D. Double Wraps Metal Connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side. E. Structural Anchor bolts structurally connected or reinforced concrete roof. F. Other: G. Unknown or unidentified H. No attic access 8. Roof Geometry: What is the roof sh			F. Unknown	or unidentified.
5 feet of the inside or outside corner of the roof in determination of WEAKEST type) A. Toe Nails Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or Metal connectors that do not meet the minimal conditions or requirements of B, C, or D Minimal conditions to qualify for categories B, C, or D. All visible metal connectors are: Secured to truss/rafter with a minimum of three (3) nails, and Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corresion. B. Clips Metal connectors that do not wrap over the top of the truss/rafter, and free of visible severe corresion. Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails. C. Single Wraps Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side. D. Double Wraps Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side. D. Bouble Wraps Metal Connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, and is secured with a minimum of 2 nails on the front side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, and is secured to the opplate with a minimum of 1 nail on the opposing side, or least the secur			G. No attic a	access.
Truss/rafter anchored to top plate of wall, or Metal connectors that do not meet the minimal conditions or requirements of B, C, or D	4.		eet of the insid	e or outside corner of the roof in determination of WEAKEST type)
the top plate of the wall, or Metal connectors that do not meet the minimal conditions or requirements of B, C, or D Minimal conditions to qualify for categories B, C, or D, All visible metal connectors are:		Ш	A. Toe Nails	
Minimal conditions to qualify for categories B, C, or D. All visible metal connectors are:				
Secured to truss/rafter with a minimum of three (3) nails, and Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ⅓" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion. B. Clips				Metal connectors that do not meet the minimal conditions or requirements of B, C, or D
Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion. B. Clips Metal connectors that do not wrap over the top of the truss/rafter, or Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails. C. Single Wraps Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side. D. Double Wraps Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or Metal Connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or Metal Connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of 1 nail on the opposing side, or Metal Connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or Metal Connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the opposing side, or Metal Connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, or Metal Connectors consisting of a single strap that wraps over the top of		Mir	nimal conditio	ons to qualify for categories B, C, or D. All visible metal connectors are:
the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion. B. Clips			\times	Secured to truss/rafter with a minimum of three (3) nails, and
Metal connectors that do not wrap over the top of the truss/rafter, or Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails. C. Single Wraps Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side. D. Double Wraps Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side. E. Structural Anchor bolts structurally connected or reinforced concrete roof. F. Other:			\boxtimes	the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe
Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails. C. Single Wraps Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side. D. Double Wraps Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side. E. Structural F. Other: G. Unknown or unidentified H. No attic access S. Roof Geometry: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification). A. Hip Roof Hip roof with no other roof shapes greater than 10% of the total roof system perimeter: Total length of non-hip features: 0		\times	B. Clips	
position requirements of C or D, but is secured with a minimum of 3 nails. C. Single Wraps Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side. D. Double Wraps Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap wraps over the top of the truss/rafter and is secured with a minimum of 1 nail on the opposing side, or embedded in the bond beam, on either uss/rafter and is secured with a minimum of 1 nail on the opposing side, or embedded in the bond beam, on either uss/rafter and is secured with a minimum of 1 nail on the opposing side, or embedded in the bond beam, on either uss/rafter and is secured with a minimum of 1 nail on the opposing side, or embedded in the bond beam, on either uss/rafter and is secured with a minimum of tree nails on each side. Restructural Problems of the truss/rafter and is sec				Metal connectors that do not wrap over the top of the truss/rafter, or
Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side. D. Double Wraps Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side. E. Structural Anchor bolts structurally connected or reinforced concrete roof. F. Other: G. Unknown or unidentified H. No attic access 5. Roof Geometry: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification). A. Hip Roof Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: 0 feet; Total roof system perimeter. Total length of non-hip features: 0 feet; Total roof system perimeter. Total length of non-hip features: 0 feet; Total roof system perimeter. Soof an a building with 5 or more units where at least 90% of the main roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft C. Other Roof Any roof that does not qualify as either (A) or (B) above. 6. Secondary Water Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to			\boxtimes	Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails.
D. Double Wraps Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side. E. Structural Anchor bolts structurally connected or reinforced concrete roof. F. Other: G. Unknown or unidentified H. No attic access S. Roof Geometry: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification). X A. Hip Roof Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: 0			C. Single Wi	Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a
Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side. E. Structural Anchor bolts structurally connected or reinforced concrete roof. F. Other: G. Unknown or unidentified H. No attic access Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side. F. Other: G. Unknown or unidentified H. No attic access G. Unknown or unidentified H. No attic access A. Hip Roof Hip roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification). X A. Hip Roof Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: 0 feet; Total roof system perimeter: 425 feet Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft C. Other Roof Any roof that does not qualify as either (A) or (B) above. 6. Secondary Water Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the		П	D. Double W	
Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side. E. Structural Anchor bolts structurally connected or reinforced concrete roof. F. Other: G. Unknown or unidentified H. No attic access Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side. A. Hore G. Unknown or unidentified H. No attic access A. Hip Roof Hip roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification). A. Hip Roof Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: 0 feet; Total roof system perimeter: 425 feet B. Flat Roof Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft C. Other Roof Any roof that does not qualify as either (A) or (B) above. 6. Secondary Water Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss. B. No SWR. C. Unknown or undetermined. Inspectors Initials CP Property Address SE Turtle Creek Dr Tequesta, FL 33469				Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with
 F. Other:				Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on
 G. Unknown or unidentified H. No attic access 5. Roof Geometry: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification). ✓ A. Hip Roof Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: 0 feet; Total roof system perimeter: 425 feet ✓ B. Flat Roof Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft ✓ C. Other Roof Any roof that does not qualify as either (A) or (B) above. 6. Secondary Water Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) ✓ A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss. ✓ B. No SWR. ✓ C. Unknown or undetermined. Inspectors Initials CP Property Address 8 SE Turtle Creek Dr Tequesta, FL 33469 				•
 H. No attic access 5. Roof Geometry: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification). ☑ A. Hip Roof Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: 0 feet; Total roof system perimeter: 425 feet Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft ☐ C. Other Roof Any roof that does not qualify as either (A) or (B) above. 6. Secondary Water Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss. ☑ B. No SWR. ☐ C. Unknown or undetermined. Inspectors Initials CP Property Address 8 SE Turtle Creek Dr Tequesta, FL 33469 		Ħ		
the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification). A. Hip Roof				
Total length of non-hip features: O feet; Total roof system perimeter: 425 feet Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft C. Other Roof Any roof that does not qualify as either (A) or (B) above. 6. Secondary Water Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss. B. No SWR. C. Unknown or undetermined. Inspectors Initials CP Property Address 8 SE Turtle Creek Dr Tequesta, FL 33469	5.			
□ B. Flat Roof Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft □ C. Other Roof Any roof that does not qualify as either (A) or (B) above. 6. Secondary Water Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) □ A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss. ☑ B. No SWR. □ C. Unknown or undetermined. Inspectors Initials CP Property Address 8 SE Turtle Creek Dr Tequesta, FL 33469		\boxtimes	A. Hip Roof	
 C. Other Roof Any roof that does not qualify as either (A) or (B) above. 6. Secondary Water Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss. ☑ B. No SWR. ☐ C. Unknown or undetermined. Inspectors Initials CP Property Address 8 SE Turtle Creek Dr Tequesta, FL 33469 			B. Flat Roof	Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of
 A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss. B. No SWR. C. Unknown or undetermined. Inspectors Initials CP Property Address 8 SE Turtle Creek Dr Tequesta, FL 33469 			C. Other Roo	
	6.	Sec	A. SWR (also sheathing dwelling) B. No SWR.	so called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the from water intrusion in the event of roof covering loss.
*This varification form is valid for up to five (5) years provided no metarial changes have been made to the structure or	In	spec	tors Initials _	CP Property Address 8 SE Turtle Creek Dr Tequesta, FL 33469
"I his verification form is valid for up to five (5) years provided no material changes have been made to the structure or	*T	his v	verification fo	orm is valid for up to five (5) years provided no material changes have been made to the structure or

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

7. Opening Protection: What is the weakest form of wind borne debris protection installed on the structure? First, use the table to determine the weakest form of protection for each category of opening. Second, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings and (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable. Non-Glazed **Opening Protection Level Chart Glazed Openings Openings** Place an "X" in each row to identify all forms of protection in use for each Windows opening type. Check only one answer below (A thru X), based on the weakest Garage Glass Entry Garage or Entry Skylights form of protection (lowest row) for any of the Glazed openings and indicate **Doors Block** Doors **Doors** Doors the weakest form of protection (lowest row) for Non-Glazed openings. Not Applicable- there are no openings of this type on the structure Α Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights) В Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights) С Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007 Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E D 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance Opening Protection products that appear to be A or B but are not verified Ν Other protective coverings that cannot be identified as A, B, or C No Windborne Debris Protection Х A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level A in the table above). Miami-Dade County PA 201, 202, and 203 Florida Building Code Testing Application Standard (TAS) 201, 202, and 203 American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996 Southern Standards Technical Document (SSTD) 12 For Skylights Only: ASTM E 1886 and ASTM E 1996 For Garage Doors Only: ANSI/DASMA 115 A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist LA.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or X in the table above A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All Glazed openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level B in the table above): ASTM E 1886 and ASTM E 1996 (Large Missile - 4.5 lb.) SSTD 12 (Large Missile – 4 lb. to 8 lb.) For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large Missile - 2 to 4.5 lb.) ☐ B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above L C. Exterior Opening Protection- Wood Structural Panels meeting FBC 2007 All Glazed openings are covered with plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above). LC.1 All Non-Glazed openings classified as A, B, or C in the table above, or no Non-Glazed openings exist LC.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in the table above C.3 One or More Non-Glazed openings is classified as Level N or X in the table above Inspectors Initials CP Property Address 8 SE Turtle Creek Dr Tequesta, FL 33469

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

N. Exterior Opening Protection (unverified shutter s protective coverings not meeting the requirements of Ar with no documentation of compliance (Level N in the ta	nswer "A", "B", or C" or sy	
N.1 All Non-Glazed openings classified as Level A, B, C, o N.2 One or More Non-Glazed openings classified as Level 1		
table above N.3 One or More Non-Glazed openings is classified as Leve	el X in the table above	
X. None or Some Glazed Openings One or more Glaze	ed openings classified and L	evel X in the table above.
MITIGATION INSPECTIONS MUST B Section 627.711(2), Florida Statutes, provi	ides a listing of individuals	
Qualified Inspector Name: CHARLIE PLAIA	License Type: HOME INSPECTOR	License or Certificate #: HI 4860
Inspection Company: BENCHMARK INSPECTIONS, INC		Phone: 888-984-4484
Oualified Inspector − I hold an active license as a Home inspector licensed under Section 468.8314, Florida Statute training approved by the Construction Industry Licensing Board Building code inspector certified under Section 468.607, Florida General, building or residential contractor licensed under Section Professional engineer licensed under Section 471.015, Florida St Professional architect licensed under Section 481.213, Florida St Any other individual or entity recognized by the insurer as posse verification form pursuant to Section 627.711(2), Florida Statute. Individuals other than licensed contractors licensed under under Section 471.015, Florida Statues, must inspect the str Licensees under s.471.015 or s.489.111 may authorize a director of the statute of	es who has completed the statut and completion of a proficienc Statutes. a 489.111, Florida Statutes. atutes. atutes. ssing the necessary qualifications. Section 489.111, Florida Statutes personally and no	tory number of hours of hurricane mitigation y exam. ons to properly complete a uniform mitigation tatutes, or professional engineer licensed of through employees or other persons.
I, CHARLIE PLAIA (print name) contractors and professional engineers only) I had my emploand I agree to be responsible for his/her work. Qualified Inspector Signature:		,
An individual or entity who knowingly or through gross ne subject to investigation by the Florida Division of Insurance appropriate licensing agency or to criminal prosecution. (Secretifies this form shall be directly liable for the misconduct performed the inspection.	gligence provides a false o e Fraud and may be subje ection 627.711(4)-(7), Flor	r fraudulent mitigation verification form is ct to administrative action by the ida Statutes) The Qualified Inspector who
Homeowner to complete: I certify that the named Qualified residence identified on this form and that proof of identification Signature:		
An individual or entity who knowingly provides or utters a obtain or receive a discount on an insurance premium to w of the first degree. (Section 627.711(7), Florida Statutes)		
The definitions on this form are for inspection purposes on as offering protection from hurricanes.	ly and cannot be used to co	ertify any product or construction feature
Inspectors Initials CP Property Address 8 SE Turtle Cre	ek Dr Tequesta, FL 3346	9
*This verification form is valid for up to five (5) years provinaccuracies found on the form.	ided no material changes	have been made to the structure or

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155

Click any of the results below to view more details.

Showing 1-10 of 13 | Download results

Application Date	Record Number	Record Type	Address	Action	<u>Status</u>	<u>Project</u> <u>Name</u>	Description	Expiration Date	Kiva Hist Ta
12/10/2020	BLD2020120605	Heating-A/C- Refrig Residential Changeout	8 SE TURTLE CREEK DR, C, JUPITER FL 33469-1531		Closed-Certificate Issued	MORAN RESIDENCE	AC CHANGE OUT		
03/05/2020	BLD2020030237	Commercial Shutters	8 SE TURTLE CREEK DR, C, JUPITER FL 33469-1531		Closed-Certificate Issued	JUPITER ALUMINUM PRODUCT	INSTALLING (1) ACCORDION SHUTTER		
10/01/2019	BLD2019100026	Heating-A/C- Refrig Residential Changeout	8 SE TURTLE CREEK DR, TEQUESTA FL 33469-5532		Closed-Certificate Issued		replace existing ac system with 15 SEER 3 ton York with 10KW heat		
07/17/2019	BLD2019070821	Commercial Shutters	8 SE TURTLE CREEK DR, B, JUPITER FL 33469-1531		Closed-Certificate Issued		ACCORDION SHUTTER TO COVER ENCLOSED PORCH		
09/18/2008	BREP2008090475	Residential Replacement Windows/Doors	8 SE TURTLE CREEK DR, TEQUESTA FL 33469-5532		DONE		REPLACE WINDOWS AN DRYWALL		T106772
08/06/2008	BRR2008080392	Residential Roofing	8 SE TURTLE CREEK DR, F, JUPITER FL 33469-1531		DONE	TURTLE CREEK	RE ROOF TILE & FLAT- BUILDING 8- COMMERCIAL		T105998
03/28/2008	BSHU2008030591	Residential Shutters	8 SE TURTLE CREEK DR, A, JUPITER FL 33469-5532		DONE		INSTALL 3 ACCORDION SHUTTERS		T103130
06/21/2006	BPL2006060766	Residential Trade Plumbing	8 SE TURTLE CREEK DR, TEQUESTA FL 33469-5532		DONE		Miscellaneous plumbing application: NEW SEWER LINE		T87302
01/31/2006	BSPW2006020526	Residential Swimming Pool With Deck	8 SE TURTLE CREEK DR, TEQUESTA FL 33469-5532		DONE		POOL WITH DECK		T81300
03/17/2005	BFEN2005031138	Residential Fence	8 SE TURTLE CREEK DR, TEQUESTA FL		DONE		INSTALL 96' OF 6' PVC FENCE		T68032

Martin County Florida Your County. Your Community.

2401 SE Monterey Road, Stuart, FL 34996

Phone (772) 288-5400





Front Elevation



Rear Elevation



8d Nails



Right Elevation



Left Elevation



19/32" Sheathing





6" Max Spacing



6" Max Spacing



6" Max Spacing



Clips





Truss 24" O.C.





Building 8